

# ANTREX Electronics

## Electronic Components Sourcing Information

---

### Product Reference Information

|                      |                           |
|----------------------|---------------------------|
| <b>Part Number:</b>  | YPCL0006T                 |
| <b>Manufacturer:</b> | Amphenol Thermometrics    |
| <b>Package:</b>      | Radial, Disc              |
| <b>Availability:</b> | Please confirm with sales |

#### Product Page:

<https://antrexco.com/product/details/amphenol-thermometrics/ypcl0006t.html>

#### Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

### Contact Information

Email: [info@antrexco.com](mailto:info@antrexco.com)

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

### Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

#### Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

## Features

- Designed for general purpose over-current, over-voltage and direct over-temperature protection
  - Wide range of operating current & voltage levels
  - Approved to CECC 44 001 - 002 (certificate E1254/F)
  - Excellent stability
  - Fail-safe operation
  - Solid state
  - High performance barium titanate ceramic
  - Suitable for automatic PCB insertion
- 

# PTC Type YP

## Thermometrics Wired Disc

PTC Type YP is a Thermometrics product. Thermometrics has joined other GE high-technology sensing businesses under a new name—GE Industrial, Sensing.



# Type YP Specifications

## Description

A range of radially-wired PTC disc thermistors with black silicone resin coating.

## Options

- Non-standard resistances and tolerances
- Resistance matching
- Non-standard wire lengths
- Other wire configurations

## Packaging

All types in the YP range are available loose-packed, as shown in the drawing. Devices are also available on bandolier (tape & reel): types with diameter  $a < 0.53$  in (13.5 mm) comply with IEC 286-2.

To identify the packaging required, replace X in the product codes shown overleaf as follows:

- **Bandoliered:** T
- **Loose-packed:** N

Devices are also available with dimension  $H_0$  (as specified in IEC 286-2) of 0.71 in (18mm) instead of the standard 0.62 in (16 mm). These parts can be ordered by adding the suffix 18 to the code e.g. YPAL0.80T18.

### Pack quantities:

- **Loose packed:** 500/box Bandoliered
- **$a < 0.53$  in (13.5 mm):** 1000/reel (0.5" pitch)
- **$a \geq 0.53$  in (13.5 mm):** 500/reel (1" pitch)

## Data

- **Tolerance on  $R_{25}$ :**  $\pm 25\%$
- **Ambient temperature range:**
  - **at maximum voltage:** 32°F to 140°F (0°C to 60°C)
  - **at zero voltage:** -13°F to 257°F (-25°C to 125°C)
  - **Lead wire material:** Solder-coated brass
  - **Body coating:** Silicone resin (except types YPEL3500X & YPEL6250X)



NTC Type JW Dimensions

# Type YP Specifications

| Group                                                        | Code      | R <sub>25</sub> | I <sub>nt</sub> | I <sub>t</sub> | I <sub>mo</sub> | I <sub>r</sub> | a    | b   | l    | d   | Brand code    | CECC approval |
|--------------------------------------------------------------|-----------|-----------------|-----------------|----------------|-----------------|----------------|------|-----|------|-----|---------------|---------------|
|                                                              |           | Ω               | A               | A              | A               | mA             | mm   | mm  | mm   | mm  |               |               |
| V <sub>max</sub> = 30 VDC<br>T <sub>b</sub> = 248°F (120°C)  | YPAL0.45X | 0.45            | 1.3             | 2.6            | 8               | 115            | 17.5 | 3.5 | 21   | 0.6 | ThM YPAL0.45  |               |
|                                                              | YPAL0.80X | 0.8             | 0.85            | 1.7            | 5.5             | 80             | 13.5 | 3.5 | 17   | 0.6 | ThM YPAL 0.80 |               |
|                                                              | YPAL1.20X | 1.2             | 0.6             | 1.2            | 4.3             | 70             | 11   | 3.5 | 14.5 | 0.6 | ThM YPAL 1.20 |               |
|                                                              | YPAL1.80X | 1.8             | 0.45            | 0.9            | 3               | 60             | 9    | 3.5 | 12.5 | 0.6 | ThM YPAL 1.80 |               |
|                                                              | YPAL4.60X | 4.6             | 0.25            | 0.5            | 1               | 45             | 6.5  | 3.5 | 10   | 0.6 | K             |               |
|                                                              | YPAL0013X | 13              | 0.12            | 0.24           | 0.7             | 25             | 4    | 3.5 | 7.5  | 0.5 | L             |               |
| V <sub>max</sub> = 80 VDC<br>T <sub>b</sub> = 176°F (80°C)   | YPBJ2.30X | 2.3             | 0.245           | 0.5            | 8               | 40             | 17.5 | 3.5 | 21   | 0.6 | ThM YPBJ 2.30 |               |
|                                                              | YPBJ3.70X | 3.7             | 0.17            | 0.35           | 5.5             | 30             | 13.5 | 3.5 | 17   | 0.6 | ThM YPBJ 3.70 |               |
|                                                              | YPBJ5.60X | 5.6             | 0.13            | 0.265          | 4.3             | 25             | 11   | 3.5 | 14.5 | 0.6 | ThM YPBJ 5.60 | Yes           |
|                                                              | YPBJ9.40X | 9.4             | 0.09            | 0.19           | 3               | 20             | 9    | 3.5 | 12.5 | 0.6 | ThM YPBJ 9.40 | Yes           |
|                                                              | YPBJ0025X | 25              | 0.05            | 0.11           | 1               | 16             | 6.5  | 3.5 | 10   | 0.6 | M             | Yes           |
|                                                              | YPBJ0055X | 55              | 0.03            | 0.06           | 0.7             | 12             | 4    | 3.5 | 7.5  | 0.5 | N             | Yes           |
| V <sub>max</sub> = 80 VDC<br>T <sub>b</sub> = 248°F (120°C)  | YPBL2.30X | 2.3             | 0.45            | 0.9            | 8               | 40             | 17.5 | 3.5 | 21   | 0.6 | ThM YPBL 2.30 |               |
|                                                              | YPBL3.70X | 3.7             | 0.32            | 0.64           | 5.5             | 30             | 13.5 | 3.5 | 17   | 0.6 | ThM YPBL 3.70 |               |
|                                                              | YPBL5.60X | 5.6             | 0.25            | 0.5            | 4.3             | 25             | 11   | 3.5 | 14.5 | 0.6 | ThM YPBL 5.60 | Yes           |
|                                                              | YPBL9.40X | 9.4             | 0.15            | 0.3            | 3               | 20             | 9    | 3.5 | 12.5 | 0.6 | ThM YPBL 9.40 | Yes           |
|                                                              | YPBL0025X | 25              | 0.085           | 0.17           | 1               | 16             | 6.5  | 3.5 | 10   | 0.6 | O             | Yes           |
|                                                              | YPBL0055X | 55              | 0.05            | 0.1            | 0.7             | 12             | 4    | 3.5 | 7.5  | 0.5 | P             | Yes           |
| V <sub>max</sub> = 265Vrms<br>T <sub>b</sub> = 176°F (80°C)  | YPCJ0006X | 6               | 0.17            | 0.35           | 4.1             | 10             | 17.5 | 5   | 21   | 0.6 | ThM YPCJ 0006 |               |
|                                                              | YPCJ0010X | 10              | 0.11            | 0.23           | 2.2             | 8              | 13.5 | 5   | 17   | 0.6 | ThM YPCJ 0010 |               |
|                                                              | YPCJ0015X | 15              | 0.09            | 0.18           | 1.5             | 6              | 11   | 5   | 14.5 | 0.6 | ThM YPCJ 0015 | Yes           |
|                                                              | YPCJ0025X | 25              | 0.06            | 0.13           | 1               | 5              | 9    | 5   | 12.5 | 0.6 | ThM YPCJ 0025 | Yes           |
|                                                              | YPCJ0070X | 70              | 0.03            | 0.07           | 0.4             | 4              | 6.5  | 5   | 10   | 0.6 | Q             | Yes           |
|                                                              | YPCJ0150X | 150             | 0.015           | 0.04           | 0.2             | 3              | 4    | 5   | 7.5  | 0.5 | R             | Yes           |
| V <sub>max</sub> = 265Vrms<br>T <sub>b</sub> = 248°F (120°C) | YPCL0006X | 6               | 0.33            | 0.66           | 4.1             | 15             | 17.5 | 5   | 21   | 0.6 | ThM YPCL 0006 |               |
|                                                              | YPCL0010X | 10              | 0.2             | 0.4            | 2.2             | 13             | 13.5 | 5   | 17   | 0.6 | ThM YPCL 0010 |               |
|                                                              | YPCL0015X | 15              | 0.14            | 0.28           | 1.5             | 10             | 11   | 5   | 14.5 | 0.6 | ThM YPCL 0015 | Yes           |
|                                                              | YPCL0025X | 25              | 0.1             | 0.2            | 1               | 9              | 9    | 5   | 12.5 | 0.6 | ThM YPCL0025  | Yes           |
|                                                              | YPCL0035X | 35              | 0.08            | 0.16           | 1               | 9              | 9    | 5   | 12.5 | 0.6 | ThM YPCL 0035 | Yes           |
|                                                              | YPCL0045X | 45              | 0.07            | 0.14           | 1               | 9              | 9    | 5   | 12.5 | 0.6 | ThM YPCL 0045 | Yes           |
|                                                              | YPCL0055X | 55              | 0.06            | 0.125          | 1               | 9              | 9    | 5   | 12.5 | 0.6 | ThM YPCL 0055 | Yes           |
|                                                              | YPCL0065X | 65              | 0.055           | 0.11           | 1               | 9              | 9    | 5   | 12.5 | 0.6 | ThM YPCL 0065 | Yes           |
|                                                              | YPCL0070X | 70              | 0.055           | 0.11           | 0.4             | 6              | 6.5  | 5   | 10   | 0.6 | S             | Yes           |
|                                                              | YPCL0120X | 120             | 0.035           | 0.07           | 0.4             | 5              | 6.5  | 5   | 10   | 0.6 | Z             | Yes           |
|                                                              | YPCL0150X | 150             | 0.03            | 0.06           | 0.2             | 5              | 4    | 5   | 7.5  | 0.5 | T             | Yes           |
| V <sub>max</sub> = 420Vrms<br>T <sub>b</sub> = 248°F (120°C) | YDDL0600X | 600             | 0.021           | 0.039          | 0.2             | 3              | 6.5  | 5   | 10   | 0.6 | U             | Yes           |
| V <sub>max</sub> = 550Vrms<br>T <sub>b</sub> = 248°F (120°C) | YPEK1200X | 1200            | 0.015           | 0.03           | 0.1             | 3              | 6.5  | 5   | 10   | 0.6 | V             | Yes           |
|                                                              | YPEK1500X | 1500            | 0.012           | 0.024          | 0.1             | 2              | 6.5  | 5   | 10   | 0.6 | W             | Yes           |
|                                                              | YPEL3500X | 3500            | 0.008           | 0.018          | 0.25            | 2.5            | 4    | 4   | 7.5  | 0.5 | X             | Yes           |
|                                                              | YPEL6250X | 6250            | 0.006           | 0.014          | 0.15            | 1.5            | 4    | 4   | 7.5  | 0.5 | Y             | Yes           |

|                  |                                                        |                 |                                            |
|------------------|--------------------------------------------------------|-----------------|--------------------------------------------|
| V <sub>max</sub> | Maximum operating voltage                              | I <sub>t</sub>  | Minimum trip current (77°F (25°C) ambient) |
| T <sub>b</sub>   | Switching temperature                                  | I <sub>mo</sub> | Maximum overload current                   |
| R <sub>25</sub>  | Resistance at 77°F (25°C)                              | I <sub>r</sub>  | Residual current (77°F (25°C) ambient)     |
| I <sub>nt</sub>  | Maximum current without tripping (77°F (25°C) ambient) |                 |                                            |

# Type YP Specifications

YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPLD0600  
YPLC0150  
YPLC0120  
YPLC0070




YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPLC0065  
YPLC0055  
YPLC0045  
YPLC0035




YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPBJ0055  
YPBJ0025  
YPBJ9.40



YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPEL6250  
YPEL3500  
YPEK1500  
YPEK1200




YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPLC0006  
YPLC0010  
YPLC0015  
YPLC0025



YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPBJ2.30  
YPBJ3.70  
YPBJ5.60



# Type YP Specifications

YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPBL0055  
YPBL0025  
YPBL9.40



YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPAL0.45  
YPAL0.80  
YPAL1.20



YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPCJ0006  
YPCJ0010  
YPCJ0015



YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPBJ2.30  
YPBJ3.70  
YPBJ5.60




YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPAL1.80  
YPAL4.60  
YPAL0013



YP types: Tripping time v Initial current  
Ta=25°C, stillair.

YPCJ0025  
YPCJ0070  
YPCJ0150



GE  
Sensing

GE  
Sensing



©2006 GE. All rights reserved.  
920-334A

All specifications are subject to change for product improvement without notice.  
GE® is a registered trademark of General Electric Co. Other company or product  
names mentioned in this document may be trademarks or registered trademarks  
of their respective companies, which are not affiliated with GE.

[www.gesensing.com](http://www.gesensing.com)