

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: BLF6G22L-40P,112

Manufacturer: Ampleon USA Inc.

Package: Please confirm with sales

Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/ampleon-usa-inc/blf6g22l-40p-112.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

BLF6G22L-40P; BLF6G22LS-40P

Power LDMOS transistor

Rev. 2 — 1 September 2015

AMPLEON

Product data sheet

1. Product profile

1.1 General description

LDMOS power transistor for base station applications at frequencies from 2110 MHz to 2170 MHz and 1805 MHz to 1880 MHz.

Table 1. Typical performance

Typical RF performance at $T_{case} = 25\text{ °C}$ in a common source class-AB production test circuit.

Mode of operation	f (MHz)	I_{DQ} (mA)	V_{DS} (V)	$P_{L(AV)}$ (W)	G_p (dB)	η_D (%)	ACPR (dBc)
2-carrier W-CDMA	2110 to 2170	410	28	13.5	19	30	-30 [2]
	1805 to 1880 [1]	410	28	5	20.3	18.3	-34.9 [2]
1-carrier W-CDMA	2110 to 2170	410	28	15	19	32	-37 [3]
	1805 to 1880 [1]	410	28	5	20.5	18.0	-42.3 [3]

[1] The performance is tested on the Class AB demo board as depicted in [Figure 11](#).

[2] Test signal: 3GPP; test model 1; 64 DPCH; PAR = 8.4 dB at 0.01 % probability on CCDF; carrier spacing 5 MHz.

[3] Test signal: 3GPP; test model 1; 64 DPCH; PAR = 7.2 dB at 0.01 % probability on CCDF.

1.2 Features and benefits





- Excellent ruggedness
- High efficiency
- Low R_{th} providing excellent thermal stability
- Lower output capacitance for improved performance in Doherty applications
- Designed for low memory effects providing excellent pre-distortability
- Internally matched for ease of use
- Integrated ESD protection
- Compliant to Directive 2002/95/EC, regarding Restriction of Hazardous Substances (RoHS)

1.3 Applications

- RF power amplifier for base stations and multi carrier applications in the 2110 MHz to 2170 MHz frequency band
- RF driver amplifier in the 1805 MHz to 1880 MHz frequency band

2. Pinning information

Table 2. Pinning

Pin	Description	Simplified outline	Graphic symbol
BLF6G22L-40P (SOT1121A)			
1	drain1		
2	drain2		
3	gate1		
4	gate2		
5	source		
[1]			
BLF6G22LS-40P (SOT1121B)			
1	drain1		
2	drain2		
3	gate1		
4	gate2		
5	source		
[1]			

[1] Connected to flange.

3. Ordering information

Table 3. Ordering information

Type number	Package		
	Name	Description	Version
BLF6G22L-40P	-	flanged LDMOST ceramic package; 2 mounting holes; 4 leads	SOT1121A
BLF6G22LS-40P	-	earless flanged LDMOST ceramic package; 4 leads	SOT1121B

4. Limiting values

Table 4. Limiting values (2 sections combined)

In accordance with the Absolute Maximum Rating System (IEC 60134).

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	drain-source voltage		-	65	V
V_{GS}	gate-source voltage		-0.5	+13	V
I_D	drain current		-	16	A
T_{stg}	storage temperature		-65	+150	°C
T_j	junction temperature		-	200	°C

5. Thermal characteristics

Table 5. Thermal characteristics

Symbol	Parameter	Conditions	Typ	Unit
$R_{th(j-c)}$	thermal resistance from junction to case	$T_{case} = 80\text{ °C}$; $P_L = 40\text{ W}$	0.7	K/W

6. Characteristics

Table 6. Characteristics (per section)

$T_j = 25\text{ °C}$; unless otherwise specified.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
$V_{(BR)DSS}$	drain-source breakdown voltage	$V_{GS} = 0\text{ V}$; $I_D = 0.4\text{ mA}$	65	-	-	V
$V_{GS(th)}$	gate-source threshold voltage	$V_{DS} = 10\text{ V}$; $I_D = 40\text{ mA}$	1.4	1.9	2.4	V
I_{DSS}	drain leakage current	$V_{GS} = 0\text{ V}$; $V_{DS} = 28\text{ V}$	-	-	2	μA
I_{DSX}	drain cut-off current	$V_{GS} = V_{GS(th)} + 3.75\text{ V}$; $V_{DS} = 10\text{ V}$	6	7	-	A
I_{GSS}	gate leakage current	$V_{GS} = 11\text{ V}$; $V_{DS} = 0\text{ V}$	-	-	200	nA
g_{fs}	forward transconductance	$V_{DS} = 10\text{ V}$; $I_D = 2.0\text{ A}$	1.8	2.9	-	S
$R_{DS(on)}$	drain-source on-state resistance	$V_{GS} = V_{GS(th)} + 3.75\text{ V}$; $I_D = 1.4\text{ A}$	0.14	0.37	0.57	Ω

7. Application information

Table 7. Application information (2 sections combined)

Mode of operation: 2-carrier W-CDMA; PAR 8.4 dB at 0.01 % probability on CCDF; 3GPP test model 1; 64 DPCH; $f_1 = 2112.5\text{ MHz}$; $f_2 = 2117.5\text{ MHz}$; $f_3 = 2162.5\text{ MHz}$; $f_4 = 2167.5\text{ MHz}$; RF performance at $V_{DS} = 28\text{ V}$; $I_{Dq} = 410\text{ mA}$; $T_{case} = 25\text{ °C}$; in a class-AB production test circuit.

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
G_p	power gain	$P_{L(AV)} = 13.5\text{ W}$	[1] 17.8	19	-	dB
RL_{in}	input return loss	$P_{L(AV)} = 13.5\text{ W}$	[1] -	-15	-9	dB
η_D	drain efficiency	$P_{L(AV)} = 13.5\text{ W}$	[1] 26.5	30	-	%
$ACPR_{5M}$	adjacent channel power ratio (5 MHz)	$P_{L(AV)} = 13.5\text{ W}$	[1] -	-30	-27	dBc
$ACPR_{10M}$	adjacent channel power ratio (10 MHz)	$P_{L(AV)} = 13.5\text{ W}$	[1] -	-39	-36	dBc


[1] In production, all testing are only performed at 2110 MHz to 2170 MHz frequency band.

7.1 Ruggedness in class-AB operation

The BLF6G22L-40P and BLF6G22LS-40P are capable of withstanding a load mismatch corresponding to VSWR = 10 : 1 through all phases under the following conditions: $V_{DS} = 28\text{ V}$; $I_{Dq} = 410\text{ mA}$; $P_L = 40\text{ W}$ (CW); $f = 2110\text{ MHz}$.


The BLF6G22L-40P and BLF6G22LS-40P are capable of withstanding a load mismatch corresponding to VSWR = 10 : 1 through all phases under the following conditions: $V_{DS} = 28\text{ V}$; $I_{Dq} = 410\text{ mA}$; $P_L = 40\text{ W}$ (CW pulse, 10 %); $f = 1842\text{ MHz}$.

7.2 CW



7.3 IS-95


Single carrier IS-95; PAR = 9.7 dB at 0.01 % probability on the CCDF.



$V_{DS} = 28 \text{ V}$; $I_{DQ} = 410 \text{ mA}$.

- (1) $f = 2110 \text{ MHz}$
- (2) $f = 2140 \text{ MHz}$
- (3) $f = 2170 \text{ MHz}$

Fig 2. Single carrier IS-95 power gain and drain efficiency as function of output power; typical values




$V_{DS} = 28 \text{ V}$; $I_{DQ} = 410 \text{ mA}$.

- (1) $f = 2110 \text{ MHz}$
- (2) $f = 2140 \text{ MHz}$
- (3) $f = 2170 \text{ MHz}$

Fig 3. Single carrier IS-95 adjacent channel power ratio as a function of output power; typical values

7.4 1-carrier W-CDMA


Test signal: 3GPP; test model 1; 64 DPCH; PAR = 7.2 dB at 0.01 % probability on CCDF.



$V_{DS} = 28 \text{ V}$; $I_{DQ} = 410 \text{ mA}$.

- (1) $f = 2112.5 \text{ MHz}$
- (2) $f = 2140 \text{ MHz}$
- (3) $f = 2167.5 \text{ MHz}$


Fig 4. 1-carrier W-CDMA power gain and drain efficiency as function of output power; typical values



$V_{DS} = 28 \text{ V}$; $I_{DQ} = 410 \text{ mA}$.

- (1) $f = 2112.5 \text{ MHz}$
- (2) $f = 2140 \text{ MHz}$
- (3) $f = 2167.5 \text{ MHz}$

Fig 5. 1-carrier W-CDMA adjacent channel power ratio as a function of output power; typical values




$V_{DS} = 28 \text{ V}$; $I_{DQ} = 410 \text{ mA}$.

- (1) $f = 2112.5 \text{ MHz}$
- (2) $f = 2140 \text{ MHz}$
- (3) $f = 2167.5 \text{ MHz}$

Fig 6. 1-carrier W-CDMA power gain and drain efficiency as function of output power; typical values

7.5 2-carrier W-CDMA


Test signal: 3GPP; test model 1; 64 DPCH; PAR = 8.4 dB at 0.01 % probability on CCDF; carrier spacing 5 MHz.



$V_{DS} = 28 \text{ V}$; $I_{Dq} = 410 \text{ mA}$.

- (1) $f = 2115 \text{ MHz}$
- (2) $f = 2140 \text{ MHz}$
- (3) $f = 2165 \text{ MHz}$


Fig 7. 2-carrier W-CDMA power gain and drain efficiency as function of output power; typical values



$V_{DS} = 28 \text{ V}$; $I_{Dq} = 410 \text{ mA}$.

- (1) $f = 2115 \text{ MHz}$
- (2) $f = 2140 \text{ MHz}$
- (3) $f = 2165 \text{ MHz}$

Fig 8. 2-carrier W-CDMA adjacent channel power ratio as a function of output power; typical values



$V_{DS} = 28 \text{ V}$; $I_{Dq} = 410 \text{ mA}$.

- (1) $f = 2115 \text{ MHz}$
- (2) $f = 2140 \text{ MHz}$
- (3) $f = 2165 \text{ MHz}$

Fig 9. 2-carrier W-CDMA peak-to-average power ratio as function of output power; typical values

8. Test information




Table 8. List of components
 See [Figure 10](#) for component layout.

Component	Description	Value	Remarks
C1, C2, C9, C10	multilayer ceramic chip capacitor	68 pF	[1]
C3, C4, C11, C12	multilayer ceramic chip capacitor	820 pF	[2]
C5, C8	multilayer ceramic chip capacitor	4.7 pF	[1]
C6, C14, C15	multilayer ceramic chip capacitor	10 μF	TDK
C13	electrolytic capacitor	470 μF ; 63 V	
R1, R2	chip resistor	12 Ω	Philips 1206

[1] American Technical Ceramics type 800B or capacitor of same quality.
 [2] American Technical Ceramics type 100A or capacitor of same quality.




Table 9. List of components

See [Figure 11](#) for component layout.

Component	Description	Value	Remarks
C1, C2, C5, C8	multilayer ceramic chip capacitor	100 nF	Murata
C3, C4, C11, C14	multilayer ceramic chip capacitor	1 μF	Murata
C6	multilayer ceramic chip capacitor	47 pF	ATC
C7	multilayer ceramic chip capacitor	10 pF	ATC
C9, C12	multilayer ceramic chip capacitor	12 pF	ATC
C10, C13	multilayer ceramic chip capacitor	330 pF	Murata
C15, C16	multilayer ceramic chip capacitor	1.5 pF	ATC
C17	multilayer ceramic chip capacitor	10 pF	ATC
C18	electrolytic capacitor	2200 μF , 50 V	Panasonic
C19, C20	multilayer ceramic chip capacitor	1 pF	ATC

Table 9. List of components
See [Figure 11](#) for component layout.

Component	Description	Value	Remarks
L1, L2	ferrite bead	5 A	Fair Rite
R1	chip resistor	500 Ω	Vishay Dale
R2, R5	chip resistor	1.1 k Ω	Vishay Dale
R3, R6	chip resistor	432 Ω	Vishay Dale
R4, R11	chip resistor	9.1 Ω	Vishay Dale
R9	chip resistor	2 k Ω	Vishay Dale
R10	chip resistor	75 Ω	Vishay Dale
R12	chip resistor	1.5 Ω	Vishay Dale
VR1	potentiometer	200 Ω	Bourns
U1	voltage regulator		NJR

9. Package outline

Flanged LDMOST ceramic package; 2 mounting holes; 4 leads

SOT1121A




Fig 12. Package outline SOT1121A

10. Abbreviations

Table 10. Abbreviations

Acronym	Description
3GPP	3rd Generation Partnership Project
CCDF	Complementary Cumulative Distribution Function
CW	Continuous Wave
DPCH	Dedicated Physical CHannel
ESD	ElectroStatic Discharge
IS-95	Interim Standard 95
LDMOS	Laterally Diffused Metal Oxide Semiconductor
LDMOST	Laterally Diffused Metal Oxide Semiconductor Transistor
PAR	Peak-to-Average power Ratio
RF	Radio Frequency
VSWR	Voltage Standing Wave Ratio
W-CDMA	Wideband Code Division Multiple Access

11. Revision history

Table 11. Revision history

Document ID	Release date	Data sheet status	Change notice	Supersedes
BLF6G22L-40P_6G22LS-40P#2	20150901	Product data sheet	-	BLF6G22L-40P_6G22LS-40P v.1
Modifications:	- The format of this document has been redesigned to comply with the new identity guidelines of Ampleon. - Legal texts have been adapted to the new company name where appropriate.			
BLF6G22L-40P_6G22LS-40P v.1	20110922	Product data sheet	-	-

12. Legal information

12.1 Data sheet status

Document status ^{[1][2]}	Product status ^[3]	Definition
Objective [short] data sheet	Development	This document contains data from the objective specification for product development.
Preliminary [short] data sheet	Qualification	This document contains data from the preliminary specification.
Product [short] data sheet	Production	This document contains the product specification.

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.ampleon.com>.

12.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Ampleon does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Ampleon sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Ampleon and its customer, unless Ampleon and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Ampleon product is deemed to offer functions and qualities beyond those described in the Product data sheet.

12.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Ampleon does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Ampleon takes no responsibility for the content in this document if provided by an information source outside of Ampleon.

In no event shall Ampleon be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Ampleon's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Ampleon.

Right to make changes — Ampleon reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Ampleon products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of an

Ampleon product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Ampleon and its suppliers accept no liability for inclusion and/or use of Ampleon products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Ampleon makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Ampleon products, and Ampleon accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Ampleon product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Ampleon does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Ampleon products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Ampleon does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Ampleon products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.ampleon.com/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Ampleon hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Ampleon products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Ampleon product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Ampleon accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Ampleon's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond Ampleon's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Ampleon for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Ampleon's standard warranty and Ampleon's product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

12.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

Any reference or use of any 'NXP' trademark in this document or in or on the surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own. Any reference or use of any 'NXP' trademark in this document or in or on the surface of Ampleon products does not result in any claim, liability or entitlement vis-à-vis the owner of this trademark. Ampleon is no longer part of the NXP group of companies and any reference to or use of the 'NXP' trademarks will be replaced by reference to or use of Ampleon's own trademarks.

13. Contact information

For more information, please visit:
<http://www.ampleon.com>

For sales office addresses, please visit:
<http://www.ampleon.com/sales>

14. Contents

1	Product profile	1
1.1	General description	1
1.2	Features and benefits	1
1.3	Applications	1
2	Pinning information	2
3	Ordering information	2
4	Limiting values	2
5	Thermal characteristics	3
6	Characteristics	3
7	Application information	3
7.1	Ruggedness in class-AB operation	3
7.2	CW	4
7.3	IS-95	5
7.4	1-carrier W-CDMA	6
7.5	2-carrier W-CDMA	7
8	Test information	8
9	Package outline	11
10	Abbreviations	13
11	Revision history	13
12	Legal information	14
12.1	Data sheet status	14
12.2	Definitions	14
12.3	Disclaimers	14
12.4	Trademarks	15
13	Contact information	15
14	Contents	16

Please be aware that important notices concerning this document and the product(s) described herein, have been included in section 'Legal information'.

© Ampleon The Netherlands B.V. 2015. All rights reserved.

For more information, please visit: <http://www.ampleon.com>
For sales office addresses, please visit: <http://www.ampleon.com/sales>

Date of release: 1 September 2015

Document identifier: BLF6G22L-40P_6G22LS-40P#2