

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information


Part Number:	MAX5111GWX+
Manufacturer:	Maxim Integrated
Package:	36-WFBGA, WLBGA
Availability:	Please confirm with sales

Product Page:

<https://antrexco.com/product/details/analog-devices-incmaxim-integrated-max5111gwx.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

MAX5111

9-Channel, 14-Bit, Current DAC with I²C Interface

Industry's First Multichannel Current-Output DAC Optimized to Bias Fiber Optic Tunable Laser Sources

 Request Full Data Sheet  Subscribe

 Active: Data sheet on request only

Related Resources



NEW
PRODUCTS



RELATED
PACKAGING



TECHNICAL
DOCS

OVERVIEW

Description

The MAX5111 is a 14-bit, 9-channel, current output digital-to-analog converter (DAC). The device operates from a low +3.0V power supply and provides 14-bit performance without any adjustment.

The device's output ranges are optimized to bias a high-power tunable laser source. Each of the 9 channels provides a current source. Connect DAC outputs in parallel to obtain additional current or to achieve higher resolution. The device contains an internal reference.

An I²C compatible interface drives the device with clock rates of up to 400kHz. An active high asynchronous CLR input resets DAC codes to zero independent of the serial interface. The device provides a separate power-supply input for driving the interface logic.

The MAX5111 is specified over a temperature range of -40°C to +105°C and are available in 3mm x 3mm 36-bump WLP and 5mm x 5mm 32-pin TQFN packages.

Key Features

- Low 3.0V Supply

Applications/Uses

- Tunable Laser Diode Biasing

- Integrated Multiplexers for Outputs 1 and 2
- Increased Current or Resolution with Outputs Connected in Parallel
- I²C-Compatible Serial Interface
- Internal Reference
- Overtemperature Protection
- -40°C to +105°C Temperature Range
- Available in 36-Bump WLP or 32-Pin TQFN Packages

© 2015 Maxim Integrated | [Contact Us](#) | [Careers](#) | [Legal](#) | [Privacy](#) | [Cookie Policy](#) | [Site Map](#)