

# ANTREX Electronics

## Electronic Components Sourcing Information

---

### Product Reference Information

**Part Number:** 2JS 250-R  
**Manufacturer:** Bel Fuse Inc.  
**Package:** Bulk  
**Availability:** Please confirm with sales

**Product Page:**

<https://antrexco.com/product/details/bel-fuse-inc/2js-250-r.html>

**Request a Quote:**

[Submit RFQ for this part](#)



Scan for product page

### Contact Information

Email: [info@antrexco.com](mailto:info@antrexco.com)

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

### Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

**Note:**

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

## Type 2JS / 3JS Time-lag Fuse Series

HF Pb 2JS/3JS Series, 5x15mm Glass Tube Time-lag Fuse

RoHS Compliant

### Description

5x15mm Time-lag, glass tube body cartridge fuse designed, approved and complied with UL and CSA standard 248-14.

### Features

- Meet UL and CSA standard 248-14
- Wide operating temperature range
- Bulk and Tape & Reel packing available
- Full compliance with EU Directive 2011/65/EU and amending directive 2015/863
- Halogen Free
- Lead Free

### Applications

Provide individual protection for components or internal circuits.

- Power supplies
- Battery charger
- Monitor
- Adapter

LEAD FREE =   
HALOGEN FREE = 



UK CA cRU US   CE

### Physical Specifications

|           |                                                                                   |
|-----------|-----------------------------------------------------------------------------------|
| Materials | Body : Glass                                                                      |
|           | Cap : Nickel Plated Brass Caps                                                    |
|           | Leads : Matte Tin Plated Copper                                                   |
| Marking   | On Fuse :                                                                         |
|           | "bel", "JS", "Current Rating", "Voltage Rating",                                  |
|           | "Appropriate Safety Logos", "✓" (RoHS compliant)                                  |
|           | On Label :                                                                        |
|           | "bel", "2JS" or "3JS", "Current Rating", "Voltage Rating", "Interrupting Rating", |
|           | "Appropriate Safety Logos" and "✓", "e" (China RoHS compliant).                   |

### Electrical Characteristics (UL/CSA STD.248-14)

| Testing Current | Blow Time |          |
|-----------------|-----------|----------|
|                 | Minimum   | Maximum  |
| 100%            | 4 hrs.    | N/A      |
| 135%            | N/A       | 1 hr.    |
| 200%            | 3 sec     | 20 sec   |
| 500%            | 100 msec  | 1.5 sec  |
| 1000%           | 30 msec   | 300 msec |

### Safety Agency Approvals

| Safety Agency                                                                       | Safety Agency Certificate | Ampere Rating/<br>Voltage Rating | Ampere Range / Volt<br>@ I.R. ability*                                     |
|-------------------------------------------------------------------------------------|---------------------------|----------------------------------|----------------------------------------------------------------------------|
|  | E20624                    | 500mA-7A<br>/350V AC             | 500mA-7A/350V AC@100A<br>500mA-7A/125V AC@10.000A<br>500mA-7A/140V DC@150A |
|                                                                                     | LR39772                   |                                  | 500mA-7A/350V AC@100A<br>500mA-7A/125V AC@10.000A                          |

\*I.R.= Interrupting Rating = Short Circuit Rating(Amps)

# Type 2JS / 3JS

2 / 4

## Environmental Specifications

|                           |                                                                                                  |
|---------------------------|--------------------------------------------------------------------------------------------------|
| Shock Resistance          | MIL-STD-202G, Method 213B, Test Condition 1 (100 G's peak for 6 milliseconds; Sawtooth waveform) |
| Vibration Resistance      | MIL-STD-202G, Method 201A (10-55 Hz, 0.06 inch, total excursion).                                |
| Salt Spray Resistance     | MIL-STD-202G, Method 101E, Test Condition B (48 hrs).                                            |
| Insulation Resistance     | MIL-STD-202G, Method 302, Test Condition A (After Opening) 10,000 ohms minimum.                  |
| Solderability             | MIL-STD-202G, Method 208H                                                                        |
| Resistance to solder Heat | MIL-STD-202G, Method 210F, Test Condition B (260+/-5°C, 10+/-1 sec)                              |
| Thermal Shock             | MIL-STD-202G, Method 107G, Test Condition B (-65°C to +125°C).                                   |
| Operating Temperature     | -55°C to +125°C                                                                                  |
| Terminal Strength         | IEC-68-2-21                                                                                      |

## Electrical Specifications

| Catalog Number | Ampere Rating | Typical Cold Resistance (ohms) | Volt-drop @100%In (Volt) max. | Voltage and Interrupting Ratings                                                        | Melting I <sup>2</sup> T <10 mSec (A <sup>2</sup> Sec) | Melting I <sup>2</sup> T @10 In (A <sup>2</sup> Sec) | Maximum Power Dissipation (W) | Agency Approvals                                                                    |                                                                                     |
|----------------|---------------|--------------------------------|-------------------------------|-----------------------------------------------------------------------------------------|--------------------------------------------------------|------------------------------------------------------|-------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|                |               |                                |                               |                                                                                         |                                                        |                                                      |                               |  |  |
| JS 500-R       | 500mA         | 0.62                           | 0.53                          | See Table of Safety Approvals on Page 1 for Voltage and associated Interrupting Ratings | 1.6                                                    | 2.0                                                  | 0.47                          | Y                                                                                   | Y                                                                                   |
| JS 600-R       | 600mA         | 0.44                           | 0.53                          |                                                                                         | 2.2                                                    | 2.3                                                  | 0.49                          | Y                                                                                   | Y                                                                                   |
| JS 700-R       | 700mA         | 0.32                           | 0.42                          |                                                                                         | 3.0                                                    | 4.0                                                  | 0.54                          | Y                                                                                   | Y                                                                                   |
| JS 750-R       | 750mA         | 0.28                           | 0.38                          |                                                                                         | 3.0                                                    | 4.0                                                  | 0.55                          | Y                                                                                   | Y                                                                                   |
| JS 800-R       | 800mA         | 0.23                           | 0.37                          |                                                                                         | 5.0                                                    | 7.0                                                  | 0.60                          | Y                                                                                   | Y                                                                                   |
| JS 1-R         | 1A            | 0.19                           | 0.36                          |                                                                                         | 5.9                                                    | 7.8                                                  | 0.64                          | Y                                                                                   | Y                                                                                   |
| JS 1.25-R      | 1.25A         | 0.13                           | 0.30                          |                                                                                         | 9.3                                                    | 12                                                   | 0.71                          | Y                                                                                   | Y                                                                                   |
| JS 1.5-R       | 1.5A          | 0.094                          | 0.23                          |                                                                                         | 15                                                     | 19                                                   | 0.80                          | Y                                                                                   | Y                                                                                   |
| JS 2-R         | 2A            | 0.063                          | 0.22                          |                                                                                         | 23                                                     | 30                                                   | 0.89                          | Y                                                                                   | Y                                                                                   |
| JS 2.5-R       | 2.5A          | 0.046                          | 0.21                          |                                                                                         | 35                                                     | 46                                                   | 0.99                          | Y                                                                                   | Y                                                                                   |
| JS 3-R         | 3A            | 0.037                          | 0.19                          |                                                                                         | 55                                                     | 72                                                   | 1.10                          | Y                                                                                   | Y                                                                                   |
| JS 3.5-R       | 3.5A          | 0.030                          | 0.18                          |                                                                                         | 69                                                     | 91                                                   | 1.16                          | Y                                                                                   | Y                                                                                   |
| JS 4-R         | 4A            | 0.026                          | 0.18                          |                                                                                         | 86                                                     | 114                                                  | 1.22                          | Y                                                                                   | Y                                                                                   |
| JS 5-R         | 5A            | 0.018                          | 0.16                          |                                                                                         | 135                                                    | 179                                                  | 1.36                          | Y                                                                                   | Y                                                                                   |
| JS 6-R         | 6A            | 0.015                          | 0.16                          |                                                                                         | 211                                                    | 279                                                  | 1.51                          | Y                                                                                   | Y                                                                                   |
| JS 7-R         | 7A            | 0.012                          | 0.15                          |                                                                                         | 263                                                    | 350                                                  | 1.60                          | Y                                                                                   | Y                                                                                   |

Consult manufacturer for other ratings



Specifications subject to change without notice

Bel Fuse Inc.  
300 Executive Drive, Suite 300,  
West Orange, NJ 07052 USA

+1 201.432.0463  
Bel.US.CS@belf.com  
[belfuse.com/circuit-protection](http://belfuse.com/circuit-protection)

# Type 2JS / 3JS

Temperature Derating Curve



Average Time Current Curve



Soldering Parameters

| Lead-free Wave Soldering Profile                   |                                              |
|----------------------------------------------------|----------------------------------------------|
| Wave Soldering Parameter                           |                                              |
| Average ramp-up rate                               | 200°C / second                               |
| Heating rate during preheat                        | typical 1 - 2°C / second<br>Max 4°C / second |
| Final preheat temperature                          | within 125°C of soldering temperature        |
| Peak temperature Tp                                | 260°C                                        |
| Time within +0°C / -5°C of actual peak temperature | 10 seconds                                   |
| Ramp-down rate                                     | 5°C / second max.                            |




# Type 2JS / 3JS

**Fuse FGNO Explanation**  
**0658 R [XXXX] -XX**  
**0658R=2JS/3JS; [XXXX]=Ampere Rating; XX=See Ordering Information as below**

| Fraction | Decimal | Milliamps | Bel FGNO[XXXX] |
|----------|---------|-----------|----------------|
| 1/2      | .500    | 500       | 0500           |
| 6/10     | .600    | 600       | 0600           |
| 7/10     | .700    | 700       | 0700           |
| 3/4      | .750    | 750       | 0750           |
| 8/10     | .800    | 800       | 0800           |


| Fraction | Decimal | Amps | Bel FGNO[XXXX] |
|----------|---------|------|----------------|
|          | 1.0     | 1    | 1000           |
| 1-1/4    | 1.25    | 1.25 | 1250           |
| 1-1/2    | 1.50    | 1.5  | 1500           |
|          | 2.0     | 2    | 2000           |
| 2-1/2    | 2.5     | 2.5  | 2500           |
|          | 3.0     | 3    | 3000           |
| 3-1/2    | 3.5     | 3.5  | 3500           |
|          | 4.0     | 4    | 4000           |
|          | 5.0     | 5    | 5000           |
|          | 6.0     | 6    | 6000           |
|          | 7.0     | 7    | 7000           |

## Mechanical Dimensions



\*Diameter lead 0.032"±0.002" for all ratings

## Ordering Information



## Packaging

| Packaging Option                           | Packaging Specification | Quantity | Packaging Code | Inside Tape Spacing |
|--------------------------------------------|-------------------------|----------|----------------|---------------------|
| Bulk (bag)                                 | N/A                     | 2000     | 01             | N/A                 |
| Bulk (Pigtail Type)                        | N/A                     | 500      | 11             | N/A                 |
| Bulk (Pigtail Type) with Insulation Sleeve | N/A                     | 500      | 41             | N/A                 |
| Tape & Reel                                | EIA-296-F               | 1500     | 12             | 10mm Pitch and 53mm |
| Tape & Reel with Insulation Sleeve         | EIA-296-F               | 1500     | 42             | 10mm Pitch and 53mm |



Specifications subject to change without notice

Bel Fuse Inc.  
300 Executive Drive, Suite 300,  
West Orange, NJ 07052 USA

+1 201.432.0463  
Bel.US.CS@belf.com  
[belfuse.com/circuit-protection](http://belfuse.com/circuit-protection)