

# ANTREX Electronics

Electronic Components Sourcing Information

---

## Product Reference Information


**Part Number:** MOV-20D621KKTR  
**Manufacturer:** Bourns Inc.  
**Package:** Disc 20mm  
**Availability:** Please confirm with sales

**Product Page:**

<https://antrexco.com/product/details/bourns-inc/mov-20d621kktr.html>

**Request a Quote:**

[Submit RFQ for this part](#)



Scan for product page

## Contact Information

Email: [info@antrexco.com](mailto:info@antrexco.com)

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

## Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

**Note:**

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

---



## Features

- High voltage and current rating
- Straight and kinked lead styles available
- Bidirectional
- Surge protection
- Fast response time
- RoHS compliant\*
- Agency listing: US

## Additional Information

Click these links for more information:



PRODUCT  
SELECTOR



TECHNICAL  
LIBRARY



INVENTORY



SAMPLES




CONTACT

## MOV-20DxxxK Series – Metal Oxide Varistor

### General Information

The MOV-20DxxxK Series of 20 mm radial leaded varistor devices protects against overvoltage transients such as lightning, power contact and power induction. The metal oxide varistors offer a choice of varistor voltages from 18 V to 1800 V and  $V_{rms}$  voltages from 11 V to 1100 V.

The devices have a high current handling, high energy absorption capability and fast response times to protect against transient faults up to rated limits.



### Industry Standard Compliance

| Standard    | UL 1449                 |
|-------------|-------------------------|
| File Number | <a href="#">E313168</a> |

### Absolute Maximum Ratings (@ $T_A = 25^\circ\text{C}$ Unless Otherwise Noted)

| Parameter                                | Symbol    | Min. | Typ. | Max. | Unit                 |
|------------------------------------------|-----------|------|------|------|----------------------|
| Operating Temperature                    | $T_{OPR}$ | -40  | 25   | +105 | $^\circ\text{C}$     |
| Storage Temperature                      | $T_{STG}$ | -40  | 25   | +125 | $^\circ\text{C}$     |
| Rated Wattage                            | $P_W$     |      |      | 1.00 | Watt                 |
| Varistor Voltage Temperature Coefficient | $V_{TC}$  | 0    |      | 0.05 | % / $^\circ\text{C}$ |
| Response Time                            | $T_r$     |      | 10   | 25   | ns                   |
| Varistor Voltage Tolerance               | $V_{tol}$ | -10  | 0    | 10   | %                    |

### Electrical Characteristics (@ $T_A = 25^\circ\text{C}$ Unless Otherwise Noted)

| Bourns Part No. | Max. Continuous Voltage (V) |      | Voltage @ 1 mA DC (V) |      |      | Voltage @ Class Current (8/20 $\mu\text{s}$ ) |                           | Max. Peak Current (8/20 $\mu\text{s}$ ) | Max. Energy (J)    | Typ. Cap. (pF) |
|-----------------|-----------------------------|------|-----------------------|------|------|-----------------------------------------------|---------------------------|-----------------------------------------|--------------------|----------------|
|                 | r.m.s.                      | d.c. | Min.                  | Nom. | Max. | Class Current (A)                             | Max. Clamping Voltage (V) | One Time                                | 8/20 $\mu\text{s}$ | 1 kHz          |
| MOV-20D180K     | 11                          | 14   | 16                    | 18   | 20   | 20                                            | 36                        | 2000                                    | 11.0               | 34200          |
| MOV-20D220K     | 14                          | 18   | 20                    | 22   | 24   | 20                                            | 43                        | 2000                                    | 14.0               | 24000          |
| MOV-20D270K     | 17                          | 22   | 24                    | 27   | 30   | 20                                            | 53                        | 2000                                    | 18.0               | 21600          |
| MOV-20D330K     | 20                          | 26   | 30                    | 33   | 36   | 20                                            | 65                        | 2000                                    | 23.0               | 19200          |
| MOV-20D390K     | 25                          | 31   | 35                    | 39   | 43   | 20                                            | 77                        | 2000                                    | 26.0               | 18000          |
| MOV-20D470K     | 30                          | 38   | 42                    | 47   | 52   | 20                                            | 93                        | 2000                                    | 33.0               | 16800          |
| MOV-20D560K     | 35                          | 45   | 50                    | 56   | 62   | 20                                            | 110                       | 2000                                    | 41.0               | 13200          |
| MOV-20D680K     | 40                          | 56   | 61                    | 68   | 75   | 20                                            | 135                       | 2000                                    | 46.0               | 10800          |
| MOV-20D820K     | 50                          | 65   | 74                    | 82   | 90   | 100                                           | 135                       | 6500                                    | 38.0               | 6000           |
| MOV-20D101K     | 60                          | 85   | 90                    | 100  | 110  | 100                                           | 165                       | 6500                                    | 45.0               | 5040           |
| MOV-20D121K     | 75                          | 100  | 108                   | 120  | 132  | 100                                           | 200                       | 6500                                    | 55.0               | 4200           |
| MOV-20D151K     | 95                          | 125  | 135                   | 150  | 165  | 100                                           | 250                       | 6500                                    | 70.0               | 3240           |
| MOV-20D181K     | 115                         | 150  | 162                   | 180  | 198  | 100                                           | 300                       | 6500                                    | 85.0               | 2640           |
| MOV-20D201K     | 130                         | 170  | 185                   | 200  | 225  | 100                                           | 340                       | 6500                                    | 95.0               | 2400           |
| MOV-20D221K     | 140                         | 180  | 198                   | 220  | 242  | 100                                           | 360                       | 6500                                    | 100.0              | 2160           |
| MOV-20D241K     | 150                         | 200  | 216                   | 240  | 264  | 100                                           | 395                       | 6500                                    | 108.0              | 1980           |
| MOV-20D271K     | 175                         | 225  | 243                   | 270  | 297  | 100                                           | 455                       | 6500                                    | 127.0              | 1800           |
| MOV-20D301K     | 190                         | 250  | 270                   | 300  | 330  | 100                                           | 500                       | 6500                                    | 136.0              | 1560           |
| MOV-20D331K     | 210                         | 275  | 297                   | 330  | 363  | 100                                           | 550                       | 6500                                    | 150.0              | 1440           |
| MOV-20D361K     | 230                         | 300  | 324                   | 360  | 396  | 100                                           | 595                       | 6500                                    | 163.0              | 1320           |
| MOV-20D391K     | 250                         | 320  | 351                   | 390  | 429  | 100                                           | 650                       | 6500                                    | 180.0              | 1200           |
| MOV-20D431K     | 275                         | 350  | 387                   | 430  | 473  | 100                                           | 710                       | 6500                                    | 190.0              | 1116           |
| MOV-20D471K     | 300                         | 385  | 423                   | 470  | 517  | 100                                           | 775                       | 6500                                    | 220.0              | 1020           |
| MOV-20D511K     | 320                         | 415  | 459                   | 510  | 561  | 100                                           | 845                       | 6500                                    | 220.0              | 936            |
| MOV-20D561K     | 350                         | 460  | 504                   | 560  | 616  | 100                                           | 925                       | 6500                                    | 220.0              | 852            |
| MOV-20D621K     | 385                         | 505  | 558                   | 620  | 682  | 100                                           | 1025                      | 6500                                    | 220.0              | 780            |
| MOV-20D681K     | 420                         | 560  | 612                   | 680  | 748  | 100                                           | 1120                      | 6500                                    | 220.0              | 720            |
| MOV-20D751K     | 460                         | 615  | 675                   | 750  | 825  | 100                                           | 1240                      | 6500                                    | 230.0              | 636            |
| MOV-20D781K     | 485                         | 640  | 702                   | 780  | 858  | 100                                           | 1290                      | 6500                                    | 255.0              | 612            |
| MOV-20D821K     | 510                         | 670  | 738                   | 820  | 902  | 100                                           | 1355                      | 6500                                    | 265.0              | 600            |
| MOV-20D911K     | 550                         | 745  | 819                   | 910  | 1001 | 100                                           | 1500                      | 6500                                    | 282.0              | 528            |
| MOV-20D102K     | 625                         | 825  | 900                   | 1000 | 1100 | 100                                           | 1650                      | 6500                                    | 310.0              | 480            |
| MOV-20D112K     | 680                         | 895  | 990                   | 1100 | 1210 | 100                                           | 1815                      | 6500                                    | 342.0              | 432            |
| MOV-20D152K     | 940                         | 1200 | 1350                  | 1500 | 1650 | 100                                           | 2475                      | 6500                                    | 383.0              | 384            |
| MOV-20D182K     | 1100                        | 1465 | 1620                  | 1800 | 1980 | 100                                           | 2970                      | 6500                                    | 625.0              | 312            |



**WARNING**  
Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\*RoHS Directive 2015/863, Mar 31, 2015 and Annex.

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

- Power supplies
- Power systems
- Line voltage
- Telecom systems
- White goods / appliances

**BOURNS®**

This is an RoHS compliant molded radial package with 100 % Sn plating on the terminations.

The drawing shows a 20D431K resistor with the following dimensions:

- Top View:**
  - Body diameter:  $23.0 \text{ (1.023) MAX.}$
  - Lead diameter:  $1.0 \pm 0.1 \text{ (.039} \pm .004\text{)}$
  - Lead length:  $10.0 \pm 0.8 \text{ (.394} \pm .031\text{)}$
  - Body height:  $H$
  - Part number: 20D431K
  - Manufacturer logo: RA
  - Lot number: 5
- Side View:**
  - Lead diameter:  $a \pm 0.1 \text{ (.039} \pm .004\text{)}$
  - Lead length:  $20.0 \text{ (.787) MIN.}$
  - Lead spacing:  $T$

**DIMENSIONS:  $\frac{\text{MM}}{\text{(INCHES)}}$**

| Bourns<br>Part Number | Dim T<br>(Max.)      | Dim H<br>(Max.)        | Dim a<br>(Typ.)      |
|-----------------------|----------------------|------------------------|----------------------|
| MOV-20D180K           | $\frac{4.2}{(.165)}$ | $\frac{26.0}{(1.024)}$ | $\frac{1.8}{(.071)}$ |
| MOV-20D220K           | $\frac{4.3}{(.169)}$ |                        | $\frac{1.8}{(.071)}$ |
| MOV-20D270K           | $\frac{4.6}{(.181)}$ |                        | $\frac{1.8}{(.071)}$ |
| MOV-20D330K           | $\frac{4.2}{(.165)}$ |                        | $\frac{1.9}{(.075)}$ |
| MOV-20D390K           | $\frac{4.4}{(.173)}$ |                        | $\frac{2.1}{(.083)}$ |
| MOV-20D470K           | $\frac{4.6}{(.181)}$ |                        | $\frac{2.3}{(.091)}$ |
| MOV-20D560K           | $\frac{4.7}{(.185)}$ |                        | $\frac{2.5}{(.098)}$ |
| MOV-20D680K           | $\frac{4.8}{(.189)}$ |                        | $\frac{2.8}{(.110)}$ |
| MOV-20D820K           | $\frac{4.2}{(.165)}$ |                        | $\frac{1.8}{(.071)}$ |
| MOV-20D101K           | $\frac{4.4}{(.173)}$ |                        | $\frac{1.9}{(.075)}$ |
| MOV-20D121K           | $\frac{4.6}{(.181)}$ |                        | $\frac{1.9}{(.075)}$ |
| MOV-20D151K           | $\frac{4.8}{(.189)}$ |                        | $\frac{2.0}{(.079)}$ |
| MOV-20D181K           | $\frac{4.0}{(.157)}$ |                        | $\frac{2.1}{(.083)}$ |
| MOV-20D201K           | $\frac{4.2}{(.165)}$ |                        | $\frac{2.2}{(.087)}$ |
| MOV-20D221K           | $\frac{4.3}{(.169)}$ |                        | $\frac{2.3}{(.091)}$ |
| MOV-20D241K           | $\frac{4.4}{(.173)}$ |                        | $\frac{2.4}{(.094)}$ |
| MOV-20D271K           | $\frac{4.6}{(.181)}$ |                        | $\frac{2.5}{(.098)}$ |
| MOV-20D301K           | $\frac{4.8}{(.189)}$ |                        | $\frac{2.7}{(.106)}$ |

| Bourns<br>Part Number | Dim T<br>(Max.)      | Dim H<br>(Max.)        | Dim a<br>(Typ.)      |
|-----------------------|----------------------|------------------------|----------------------|
| MOV-20D331K           | $\frac{5.0}{(.197)}$ | $\frac{26.0}{(1.024)}$ | $\frac{2.8}{(.110)}$ |
| MOV-20D361K           | $\frac{5.2}{(.205)}$ |                        | $\frac{2.9}{(.114)}$ |
| MOV-20D391K           | $\frac{5.4}{(.213)}$ |                        | $\frac{3.1}{(.122)}$ |
| MOV-20D431K           | $\frac{5.6}{(.220)}$ |                        | $\frac{3.3}{(.130)}$ |
| MOV-20D471K           | $\frac{5.9}{(.232)}$ |                        | $\frac{3.4}{(.134)}$ |
| MOV-20D511K           | $\frac{6.0}{(.236)}$ |                        | $\frac{3.7}{(.146)}$ |
| MOV-20D561K           | $\frac{6.5}{(.256)}$ | $\frac{28.0}{(1.102)}$ | $\frac{3.9}{(.154)}$ |
| MOV-20D621K           | $\frac{6.9}{(.272)}$ |                        | $\frac{4.1}{(.161)}$ |
| MOV-20D681K           | $\frac{7.0}{(.276)}$ |                        | $\frac{4.2}{(.165)}$ |
| MOV-20D751K           | $\frac{7.2}{(.283)}$ |                        | $\frac{4.4}{(.173)}$ |
| MOV-20D781K           | $\frac{7.4}{(.291)}$ |                        | $\frac{4.4}{(.173)}$ |
| MOV-20D821K           | $\frac{7.8}{(.307)}$ |                        | $\frac{4.6}{(.181)}$ |
| MOV-20D911K*          | $\frac{8.2}{(.323)}$ |                        | $\frac{4.6}{(.181)}$ |
| MOV-20D102K*          | $\frac{8.7}{(.343)}$ |                        | $\frac{4.8}{(.189)}$ |
| MOV-20D112K*          | $\frac{9.2}{(.362)}$ |                        | $\frac{5.2}{(.205)}$ |
| MOV-20D152K**         |                      | N/A                    |                      |
| MOV-20D182K**         |                      | N/A                    |                      |

\*\* Not available in Straight Lead configuration; see Kinked Leads (In-line) configuration.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

# MOV-20DxxxK Series – Metal Oxide Varistor

**BOURNS®**

## Product Dimensions (Continued)

This is an RoHS compliant molded radial package with 100 % Sn plating on the terminations.

### Kinked Leads (Outward)



| Bourns Part Number | Dim T (Max.)         | Dim H (Max.)    | Dim a (Typ.)         |
|--------------------|----------------------|-----------------|----------------------|
| MOV-20D180KK       | $\frac{4.2}{(.165)}$ | 28.0<br>(1.102) | $\frac{1.8}{(.071)}$ |
| MOV-20D220KK       | $\frac{4.3}{(.169)}$ |                 | $\frac{1.8}{(.071)}$ |
| MOV-20D270KK       | $\frac{4.6}{(.181)}$ |                 | $\frac{1.8}{(.071)}$ |
| MOV-20D330KK       | $\frac{4.2}{(.165)}$ |                 | $\frac{1.9}{(.075)}$ |
| MOV-20D390KK       | $\frac{4.4}{(.173)}$ |                 | $\frac{2.1}{(.083)}$ |
| MOV-20D470KK       | $\frac{4.6}{(.181)}$ |                 | $\frac{2.3}{(.091)}$ |
| MOV-20D560KK       | $\frac{4.7}{(.185)}$ |                 | $\frac{2.5}{(.098)}$ |
| MOV-20D680KK       | $\frac{4.8}{(.189)}$ |                 | $\frac{2.8}{(.110)}$ |
| MOV-20D820KK       | $\frac{4.2}{(.165)}$ |                 | $\frac{1.8}{(.071)}$ |
| MOV-20D101KK       | $\frac{4.4}{(.173)}$ |                 | $\frac{1.9}{(.075)}$ |
| MOV-20D121KK       | $\frac{4.6}{(.181)}$ |                 | $\frac{1.9}{(.075)}$ |
| MOV-20D151KK       | $\frac{4.8}{(.189)}$ |                 | $\frac{2.0}{(.079)}$ |
| MOV-20D181KK       | $\frac{4.0}{(.157)}$ |                 | $\frac{2.1}{(.083)}$ |
| MOV-20D201KK       | $\frac{4.2}{(.165)}$ |                 | $\frac{2.2}{(.087)}$ |
| MOV-20D221KK       | $\frac{4.3}{(.169)}$ |                 | $\frac{2.3}{(.091)}$ |
| MOV-20D241KK       | $\frac{4.4}{(.173)}$ |                 | $\frac{2.4}{(.094)}$ |
| MOV-20D271KK       | $\frac{4.6}{(.181)}$ |                 | $\frac{2.5}{(.098)}$ |
| MOV-20D301KK       | $\frac{4.8}{(.189)}$ |                 | $\frac{2.7}{(.106)}$ |

| Bourns Part Number | Dim T (Max.)         | Dim H (Max.)                                           | Dim a (Typ.)         |
|--------------------|----------------------|--------------------------------------------------------|----------------------|
| MOV-20D331KK       | $\frac{5.0}{(.197)}$ | 28.0<br>(1.102)                                        | $\frac{2.8}{(.110)}$ |
| MOV-20D361KK       | $\frac{5.2}{(.205)}$ |                                                        | $\frac{2.9}{(.114)}$ |
| MOV-20D391KK       | $\frac{5.4}{(.213)}$ |                                                        | $\frac{3.1}{(.122)}$ |
| MOV-20D431KK       | $\frac{5.6}{(.220)}$ |                                                        | $\frac{3.3}{(.130)}$ |
| MOV-20D471KK       | $\frac{5.9}{(.232)}$ |                                                        | $\frac{3.4}{(.134)}$ |
| MOV-20D511KK       | $\frac{6.0}{(.236)}$ | 30.0<br>(1.181)                                        | $\frac{3.7}{(.146)}$ |
| MOV-20D561KK       | $\frac{6.5}{(.256)}$ |                                                        | $\frac{3.9}{(.154)}$ |
| MOV-20D621KK       | $\frac{6.9}{(.272)}$ |                                                        | $\frac{4.1}{(.161)}$ |
| MOV-20D681KK       | $\frac{7.0}{(.276)}$ |                                                        | $\frac{4.2}{(.165)}$ |
| MOV-20D751KK       | $\frac{7.2}{(.283)}$ |                                                        | $\frac{4.4}{(.173)}$ |
| MOV-20D781KK       | $\frac{7.4}{(.291)}$ | N/A<br><br>See Kinked Leads<br>(In-line) Configuration | $\frac{4.4}{(.173)}$ |
| MOV-20D821KK       |                      |                                                        |                      |
| MOV-20D911KK*      |                      |                                                        |                      |
| MOV-20D102KK*      |                      |                                                        |                      |
| MOV-20D112KK*      |                      |                                                        |                      |
| MOV-20D152KK*      |                      |                                                        |                      |
| MOV-20D182KK*      |                      |                                                        |                      |

\* Not available in Tape & Reel packaging.

(Kinked Lead Product Dimensions continue on page 4.)

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

# MOV-20DxxxK Series – Metal Oxide Varistor

**BOURNS®**

## Product Dimensions (Continued)

This is an RoHS compliant molded radial package with 100 % Sn plating on the terminations.

### Kinked Leads (In-line)



| Bourns Part Number | Dim T (Max.)                                    |
|--------------------|-------------------------------------------------|
| MOV-20D180KK       | N/A<br>See Kinked Leads (Outward) Configuration |
| MOV-20D220KK       |                                                 |
| MOV-20D270KK       |                                                 |
| MOV-20D330KK       |                                                 |
| MOV-20D390KK       |                                                 |
| MOV-20D470KK       |                                                 |
| MOV-20D560KK       |                                                 |
| MOV-20D680KK       |                                                 |
| MOV-20D820KK       |                                                 |
| MOV-20D101KK       |                                                 |
| MOV-20D121KK       |                                                 |
| MOV-20D151KK       |                                                 |
| MOV-20D181KK       |                                                 |
| MOV-20D201KK       |                                                 |
| MOV-20D221KK       |                                                 |
| MOV-20D241KK       |                                                 |
| MOV-20D271KK       |                                                 |
| MOV-20D301KK       |                                                 |

| Bourns Part Number | Dim T (Max.)                                    |
|--------------------|-------------------------------------------------|
| MOV-20D331KK       | N/A<br>See Kinked Leads (Outward) Configuration |
| MOV-20D361KK       |                                                 |
| MOV-20D391KK       |                                                 |
| MOV-20D431KK       |                                                 |
| MOV-20D471KK       |                                                 |
| MOV-20D511KK       |                                                 |
| MOV-20D561KK       |                                                 |
| MOV-20D621KK       |                                                 |
| MOV-20D681KK       |                                                 |
| MOV-20D751KK       |                                                 |
| MOV-20D781KK       |                                                 |
| MOV-20D821KK       |                                                 |
| MOV-20D911KK*      |                                                 |
| MOV-20D102KK*      |                                                 |
| MOV-20D112KK*      |                                                 |
| MOV-20D152KK*      |                                                 |
| MOV-20D182KK*      |                                                 |

\* Not available in Tape & Reel packaging.

## Typical Part Marking

| Bourns Part Number | Bourns Part Marking |
|--------------------|---------------------|
| MOV-20D180K        | 20D180K             |
| MOV-20D220K        | 20D220K             |
| MOV-20D270K        | 20D270K             |
| MOV-20D330K        | 20D330K             |
| MOV-20D390K        | 20D390K             |
| MOV-20D470K        | 20D470K             |
| MOV-20D560K        | 20D560K             |
| MOV-20D680K        | 20D680K             |
| MOV-20D820K        | 20D820K             |
| MOV-20D101K        | 20D101K             |
| MOV-20D121K        | 20D121K             |
| MOV-20D151K        | 20D151K             |
| MOV-20D181K        | 20D181K             |
| MOV-20D201K        | 20D201K             |
| MOV-20D221K        | 20D221K             |
| MOV-20D241K        | 20D241K             |
| MOV-20D271K        | 20D271K             |
| MOV-20D301K        | 20D301K             |
| MOV-20D331K        | 20D331K             |
| MOV-20D361K        | 20D361K             |
| MOV-20D391K        | 20D391K             |
| MOV-20D431K        | 20D431K             |
| MOV-20D471K        | 20D471K             |
| MOV-20D511K        | 20D511K             |
| MOV-20D561K        | 20D561K             |
| MOV-20D621K        | 20D621K             |
| MOV-20D681K        | 20D681K             |
| MOV-20D751K        | 20D751K             |
| MOV-20D781K        | 20D781K             |
| MOV-20D821K        | 20D821K             |
| MOV-20D911K        | 20D911K             |
| MOV-20D102K        | 20D102K             |
| MOV-20D112K        | 20D112K             |
| MOV-20D152K        | 20D152K             |
| MOV-20D182K        | 20D182K             |

NOTE: The "5" marking on MOV products is for traceability of production assembly for quality assurance compliance.

Specifications are subject to change without notice. Users should verify actual device performance in their specific applications. The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

## MOV-20DxxxK Series – Metal Oxide Varistor

**BOURNS®**

### How to Order

MOV - 20D nn (n) K (TR)

Model Designator \_\_\_\_\_  
MOV = Metal Oxide Varistor

Disc Diameter \_\_\_\_\_  
20D = 20 mm

Nominal Varistor Voltage \_\_\_\_\_  
See Electrical Characteristics Table

Multiplier of Voltage Digits \_\_\_\_\_  
0 = No multiplier  
1 = nn \* 10<sup>1</sup>  
2 = nn \* 10<sup>2</sup>

Varistor Voltage Tolerance \_\_\_\_\_  
K = 10 %

Lead Style \_\_\_\_\_  
Blank = Straight Leads  
K = Kinked Leads

Packaging \_\_\_\_\_  
Blank = Bulk  
TR = Tape & Reel\*

Examples: MOV-20D270KK = 27 V, Kinked Leads, Bulk Pack

MOV-20D331KTR = 330 V, Straight Leads, Tape & Reel

\* Models MOV-20D911K, 102K, 112K, 152K and 182K are not available in Tape & Reel packaging.

### Environmental Specifications

Moisture Sensitivity Level ..... 1  
ESD Classification (HBM)..... N/A

### Internal Construction



Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

# MOV-20DxxxK Series – Metal Oxide Varistor

**BOURNS®**

## Performance Graphs

### V-I Characteristics

**MOV-20D180K to MOV-20D680K**



**MOV-20D820K to MOV-20D431K**



**MOV-20D471K to MOV-20D182K**



Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

## MOV-20DxxxK Series – Metal Oxide Varistor

**BOURNS®**

### Pulse Rating Curves



Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

# MOV-20DxxxK Series – Metal Oxide Varistor

**BOURNS®**

## Packaging Information

### TAPE & REEL - Straight Leads



| Item                                 | Symbol     | 20 mm Disc                              |
|--------------------------------------|------------|-----------------------------------------|
| Reel Outside Diameter                | RD         | $\frac{355}{(13.98)}$                   |
| Reel Inner Diameter                  | RD1        | $\frac{30}{(1.181)}$                    |
| Tape Width                           | RW         | $\frac{55}{(2.16)}$                     |
| Reel Width                           | RW1        | $\frac{63}{(2.48)} \text{ max.}$        |
| Pitch of Component                   | P          | $\frac{25.4 \pm 1.0}{(1.00 \pm 0.04)}$  |
| Feed Hole Pitch                      | P0         | $\frac{12.7 \pm 0.2}{(0.50 \pm 0.008)}$ |
| Feed Hole Center to Pitch            | P1         | $\frac{7.77 \pm 0.7}{(0.31 \pm 0.03)}$  |
| Feed Hole Center to Component Center | P2         | $\frac{12.7 \pm 0.7}{(0.50 \pm 0.03)}$  |
| Lead to Lead Distance                | F          | $\frac{10.0 \pm 0.8}{(0.39 \pm 0.03)}$  |
| Component Alignment                  | $\Delta h$ | $\frac{4.0}{(0.16)} \text{ max.}$       |
| Tape Width                           | W          | $\frac{18.0 \pm 0.5}{(0.71 \pm 0.02)}$  |
| Hole Down Tape Width                 | W0         | $\frac{12.0 \pm 0.8}{(0.47 \pm 0.03)}$  |
| Hole Position                        | W1         | $\frac{9.0 \pm 0.5}{(0.35 \pm 0.02)}$   |
| Hole Down Tape Position              | W2         | $\frac{3.0}{(0.12)} \text{ max.}$       |
| Height From Center to Component Base | H          | $\frac{19.0 \pm 1.0}{(0.75 \pm 0.04)}$  |
| Component Height                     | H1         | $\frac{47.0}{(1.85)} \text{ max.}$      |
| Feed Hole Diameter                   | D0         | $\frac{4.0 \pm 0.2}{(0.16 \pm 0.008)}$  |
| Total Tape Thickness                 | t          | $\frac{0.6 \pm 0.3}{(0.02 \pm 0.01)}$   |
| Quantity per Reel                    | -          | 250                                     |

NOTE: Models MOV-20D911K, 102K, 112K, 152K and 182K are not available in Tape & Reel packaging.

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

# MOV-20DxxxK Series – Metal Oxide Varistor

**BOURNS®**

## Packaging Information (Continued)


### TAPE & REEL - Kinked Leads



NOTE: Models MOV-20D911KK, 102KK, 112KK, 152KK and 182KK are not available in Tape & Reel packaging.

| Item                                                          | Symbol     | 20 mm Disc                              |
|---------------------------------------------------------------|------------|-----------------------------------------|
| Reel Outside Diameter                                         | RD         | $\frac{355}{(13.98)}$                   |
| Reel Inner Diameter                                           | RD1        | $\frac{30}{(1.181)}$                    |
| Tape Width                                                    | RW         | $\frac{55}{(2.16)}$                     |
| Reel Width                                                    | RW1        | $\frac{63}{(2.48)}$ max.                |
| Pitch of Component                                            | P          | $\frac{25.4 \pm 1.0}{(1.00 \pm 0.04)}$  |
| Feed Hole Pitch                                               | P0         | $\frac{12.7 \pm 0.2}{(0.50 \pm 0.008)}$ |
| Feed Hole Center to Pitch                                     | P1         | $\frac{7.77 \pm 0.7}{(0.31 \pm 0.03)}$  |
| Feed Hole Center to Component Center                          | P2         | $\frac{12.7 \pm 0.7}{(0.50 \pm 0.03)}$  |
| Lead to Lead Distance                                         | F          | $\frac{10.0 \pm 0.8}{(0.39 \pm 0.03)}$  |
| Component Alignment                                           | $\Delta h$ | $\frac{4.0}{(0.157)}$ max.              |
| Tape Width                                                    | W          | $\frac{18.0 \pm 0.5}{(0.71 \pm 0.02)}$  |
| Hole Down Tape Width                                          | W0         | $\frac{12.0 \pm 0.8}{(0.47 \pm 0.03)}$  |
| Hole Position                                                 | W1         | $\frac{9.0 \pm 0.5}{(0.35 \pm 0.02)}$   |
| Hole Down Tape Position                                       | W2         | $\frac{3.0}{(0.12)}$ max.               |
| Height From Component Top to Kinked Base (MOV-20D180KK~511KK) | H          | $\frac{28.0}{(1.10)}$ max.              |
| Height From Component Top to Kinked Base (MOV-20D561KK~821KK) | H          | $\frac{30.0}{(1.18)}$ max.              |
| Seating Plane Height                                          | H0         | $\frac{16.0 \pm 0.5}{(0.63 \pm 0.02)}$  |
| Component Height                                              | H1         | $\frac{47.0}{(1.85)}$ max.              |
| Feed Hole Diameter                                            | D0         | $\frac{4.0 \pm 0.2}{(0.16 \pm 0.08)}$   |
| Total Tape Thickness                                          | t          | $\frac{0.6 \pm 0.3}{(0.02 \pm 0.01)}$   |
| Quantity per Reel                                             | -          | 250                                     |

### BULK



QUANTITY:  
 MOV-20D180K – 20D301K = 500 PCS. PER BOX  
 MOV-20D331K – 20D431K = 400 PCS. PER BOX  
 MOV-20D471K – 20D821K = 300 PCS. PER BOX  
 MOV-20D911K – 20D182K = 200 PCS. PER BOX



**BOURNS®**

**Americas:** Tel: +1 951-781-5500  
 Email: [americus@bourns.com](mailto:americus@bourns.com)

**Mexico:** Tel: +52-614-478-0400  
 Email: [mexicus@bourns.com](mailto:mexicus@bourns.com)

**Asia:** Tel: +886-2-2562-4117  
 Email: [asiacus@bourns.com](mailto:asiacus@bourns.com)

**EMEA:** Tel: +36 88 885 877  
 Email: [eurocus@bourns.com](mailto:eurocus@bourns.com)

[www.bourns.com](http://www.bourns.com)

REV. 07/25

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain "typical" applications are based on Bourns' knowledge of typical requirements in generic applications. Bourns assumes that "typical" applications include failsafe/backup features to address critical risks to users and are designed to allow rework of Bourns® product to avoid scrap of a device solely due to malfunctioning Bourns® product. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Thus, users should always verify the actual performance of the Bourns® product in their specific devices and applications and make their own independent judgments regarding the suitability of Bourns® product and the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real-world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification even if such industry standard or qualification is a "state of art". Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage, such as without limitation nuclear, life-critical medical and certain automotive and aviation applications. Except as set forth in the bullet points below or unless expressly and specifically approved in writing on a case-by-case basis by an authorized Bourns' representative, use of any Bourns® products in such unauthorized high-risk applications is at the user's sole risk.

- Bourns considers implantable/invasive devices and devices/procedures designed as life-supporting or life-sustaining by the U.S. Food and Drug Administration or equivalent organizations outside of the United States as "life-critical" medical applications. Bourns expressly identifies those Bourns® standard products that are suitable for use in typical medical applications that are not life-critical in its publication entitled "Bourns Medical Grade Component Guide."
- Bourns expressly identifies those Bourns® standard products that are suitable for use in typical automotive applications associated with any Automate Safety Integrity Level (ASIL) in its publication entitled "Bourns Automotive Grade Component Guide." Bourns' designation of Bourns® product as compliant with the AEC-Q standard does not by itself mean that Bourns has approved such product for use in an automotive application.
- Bourns expressly identifies Bourns® standard products that are suitable for use in the typical aviation applications/systems requiring System Design Assurance Level (RTCA DO-254 DAL) of C, D or E in its publication entitled "Bourns Civilian Aerospace/Aviation Grade Component Guide." Bourns does not test its products for compliance with United States Federal Aviation Administration standards or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aviation applications. Use of Bourns® standard components in aviation applications associated with RTCA DO-254 DAL A or B without proper approval noted above shall be at the user's sole risk.
- Bourns will review and authorize on a case-by-case basis the use of Bourns® standard products which are at least AEC-Q compliant in space-related civil applications (rockets, satellites) with a negotiated cross-waiver and indemnity agreement.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Use of Bourns® products or Bourns' technology in military/defense applications must be reviewed with Bourns for compliance with applicable export control laws and embargoes. Users shall not sell, transfer, export or re-export (which includes transfers within a country) any Bourns® products or technology or technical data for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology or technical data in any facility which engages in activities relating to such devices. Further, Bourns® products and Bourns' technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products and technology may not, without prior authorization from Bourns and/or the Government of a country where such product/technology is designed and/or manufactured, be resold, transferred, or re-exported (including within the same country) to any party not eligible to receive commodities, software, and technical data originating in such country.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties (those not based on parameters specified in Bourns' data sheets and/or specifications), including implied warranties of fitness for particular purpose, non-infringement and merchantability.

*For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:*

Web Page: <https://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <https://www.bourns.com/docs/Legal/disclaimer.pdf>