

# ANTREX Electronics

## Electronic Components Sourcing Information

---

### Product Reference Information

|                      |                                             |
|----------------------|---------------------------------------------|
| <b>Part Number:</b>  | SF-0603HI200F-2                             |
| <b>Manufacturer:</b> | Bourns Inc.                                 |
| <b>Package:</b>      | Tape & Reel (TR), Cut Tape (CT), Digi-Reel® |
| <b>Availability:</b> | Please confirm with sales                   |

**Product Page:**

<https://antrexco.com/product/details/bourns-inc/sf-0603hi200f-2.html>

**Request a Quote:**

[Submit RFQ for this part](#)



Scan for product page

### Contact Information

Email: [info@antrexco.com](mailto:info@antrexco.com)

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

### Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

**Note:**

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.



## SinglFuse™ SF-0603HI-F Series Features

- Single blow fuse for overcurrent protection
- 1608 (EIA 0603) miniature footprint
- High inrush current withstand fuse
- UL 248-14 compliant
- RoHS compliant\* and halogen free\*\*
- Thin film chip design
- Surface mount packaging for automated assembly

### SF-0603HI-F Series - High Inrush Current Withstand Surface Mount Fuses

#### Clearing Time Characteristics for Series

| % of Current Rating | Clearing Time at 25 °C |              |
|---------------------|------------------------|--------------|
|                     | Min.                   | Max.         |
| 100 %               | 4 hours                | —            |
| 200 %               | 1 second               | 60 seconds   |
| 1000 %              | 0.0002 seconds         | 0.02 seconds |

#### Additional Information

Click these links for more information:



[PRODUCT  
SELECTOR](#)



[TECHNICAL  
LIBRARY](#)



[INVENTORY](#)



[SAMPLES](#)



[CONTACT](#)

#### Electrical Characteristics

| Model           | Rated Current (A) | Resistance (Ω) Typ.*** | Rated Voltage | Interrupting Rating                                              | Typical I <sup>2</sup> t (A <sup>2</sup> s)**** | Certifications               |
|-----------------|-------------------|------------------------|---------------|------------------------------------------------------------------|-------------------------------------------------|------------------------------|
|                 |                   |                        |               |                                                                  |                                                 | cUL: <a href="#">E198545</a> |
| SF-0603HI050F-2 | 0.50              | 0.1550                 | 65 VDC        | 50 A @ 35 VAC<br>13 A @ 65 VDC<br>50 A @ 35 VDC                  | 0.019                                           | ✓                            |
| SF-0603HI075F-2 | 0.75              | 0.0830                 |               |                                                                  | 0.036                                           | ✓                            |
| SF-0603HI100F-2 | 1.00              | 0.0500                 |               |                                                                  | 0.052                                           | ✓                            |
| SF-0603HI150F-2 | 1.50              | 0.0290                 |               |                                                                  | 0.110                                           | ✓                            |
| SF-0603HI200F-2 | 2.00              | 0.0200                 | 35 VDC        | 35 A @ 35 VAC<br>50 A @ 24 VAC<br>35 A @ 35 VDC<br>50 A @ 24 VDC | 0.310                                           | ✓                            |
| SF-0603HI250F-2 | 2.50              | 0.0165                 |               |                                                                  | 0.400                                           | ✓                            |
| SF-0603HI300F-2 | 3.00              | 0.0140                 |               |                                                                  | 0.600                                           | ✓                            |
| SF-0603HI350F-2 | 3.50              | 0.0120                 |               |                                                                  | 0.800                                           | ✓                            |
| SF-0603HI400F-2 | 4.00              | 0.0095                 |               |                                                                  | 1.200                                           | ✓                            |

\*\*\* Resistance value measured with ≤10 % rated current at 25 °C ambient. Tolerance ±25 %.

\*\*\*\* Melting I<sup>2</sup>t calculated at 0.001 second pre-arcing time.

# BOURNS®

**Asia-Pacific:** Tel: +886-2 2562-4117 • Email: [asiacus@bourns.com](mailto:asiacus@bourns.com)

**EMEA:** Tel: +36 88 885 877 • Email: [eurocus@bourns.com](mailto:eurocus@bourns.com)

**The Americas:** Tel: +1-951 781-5500 • Email: [americus@bourns.com](mailto:americus@bourns.com)

[www.bourns.com](http://www.bourns.com)



**WARNING Cancer  
and Reproductive Harm**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

\*RoHS Directive 2015/863, Mar 31, 2015 and Annex.

\*\*Bourns considers a product to be "halogen free" if (a) the Bromine (Br) content is 900 ppm or less; (b) the Chlorine (Cl) content is 900 ppm or less; and (c) the total Bromine (Br) and Chlorine (Cl) content is 1500 ppm or less.

"SinglFuse" is a trademark of Bourns, Inc.

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).


## SinglFuse™ SF-0603HI-F Series Applications

- Portable memory
- LCD monitors
- Disk drives
- PDAs
- Digital cameras
- MP3 players
- Cell phones
- Rechargeable battery packs
- Battery chargers
- Set-top boxes
- Industrial controllers
- Battery Management Systems (BMS)
- LED lighting
- Power tools


### SF-0603HI-F Series - High Inrush Current Withstand Surface Mount Fuses

**BOURNS®**

**Average Pre-Arcing Time vs. Current Curves**



**Average  $I^2t$  vs.  $t$  Curves**



### Environmental Characteristics

|                                  |                                 |
|----------------------------------|---------------------------------|
| Operating Temperature.....       | -55 °C to +90 °C                |
| Storage Conditions               |                                 |
| Temperature .....                | +5 °C to +35 °C                 |
| Humidity.....                    | 40 % to 75 %                    |
| Shelf Life.....                  | 2 years from manufacturing date |
| Moisture Sensitivity Level ..... | 1                               |
| ESD Classification (HBM).....    | Class 6                         |

Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

## SF-0603HI-F Series - High Inrush Current Withstand Surface Mount Fuses

**BOURNS®**

### Typical Part Marking

Represents total content. Layout may vary.



RATED CURRENT (A)  
 C = 0.50 J = 2.50  
 D = 0.75 L = 3.00  
 E = 1.00 N = 3.50  
 T = 1.50 P = 4.00  
 F = 2.00

### How to Order


**SF - 0603 HI 015 F - 2**

SinglFuse™  
 Product Designator  
 SMD Footprint  
 0603 = 1608 (EIA 0603) size  
 Fuse Blow Type  
 HI = High Inrush Current Withstand  
 Rated Current  
 050 ~ 400 (500 mA ~ 4.0 A)  
 Structure Type  
 F = Thin film  
 Packaging Type  
 - 2 = Tape & Reel


### Packaging

|                |                      |
|----------------|----------------------|
| Reel Dimension | 7-inch Tape and Reel |
| Specification  | EIA 481-2            |
| Quantity       | 8,000 pieces         |
| Packaging Code | -2                   |


### Recommended Pad Layout



### Product Dimensions




### Current Rating Thermal Derating Curve



Specifications are subject to change without notice.

Users should verify actual device performance in their specific applications.

The products described herein and this document are subject to specific legal disclaimers as set forth on the last page of this document, and at [www.bourns.com/docs/legal/disclaimer.pdf](http://www.bourns.com/docs/legal/disclaimer.pdf).

**Solder Reflow Recommendations**

| Profile Feature                                                                                                                           | Pb-Free Assembly                   |
|-------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| Preheat / Soak:<br>Temperature Min. ( $T_{smin}$ )<br>Temperature Max. ( $T_{smax}$ )<br>Time ( $t_s$ ) from ( $T_{smin}$ to $T_{smax}$ ) | 150 °C<br>200 °C<br>60~120 seconds |
| Ramp Up Rate ( $T_L$ to $T_p$ )                                                                                                           | 3 °C / second max.                 |
| Liquidous Temperature ( $T_L$ )<br>Time ( $t_L$ ) maintained above $T_L$                                                                  | 217 °C<br>60~150 seconds           |
| Peak Package Body Temperature ( $T_p$ )                                                                                                   | 260 °C                             |
| Time ( $t_p$ )* within 5 °C of the specified classification temperature ( $T_c$ )                                                         | 30 seconds*                        |
| Ramp Down Rate ( $T_p$ to $T_L$ )                                                                                                         | 6 °C / second max.                 |
| Time 25 °C to Peak Temperature                                                                                                            | 8 minutes max.                     |

\* Tolerance for peak profile temperature ( $T_p$ ) is defined as a supplier minimum and a user maximum.

**Reliability Testing**

| No. | Test                 | Requirement                                                                                                | Test Condition                                                                     | Test Reference         |
|-----|----------------------|------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|------------------------|
| 1   | Bending              | $\leq 1$ A: DCR change $\leq \pm 10\%$<br>$> 1$ A: DCR change $\leq \pm 20\%$                              | 2 mm                                                                               | Refer to STP document  |
| 2   | Solderability        | Minimum 95 % coverage                                                                                      | One dip at 255 °C for 5 seconds                                                    | MIL-STD-202 Method 208 |
| 3   | Thermal shock        | DCR change $\leq \pm 10\%$<br>No mechanical damage                                                         | 100 cycles between -55 °C and +125 °C                                              | MIL-STD-202 Method 107 |
| 4   | Moisture resistance  | DCR change $\leq \pm 10\%$<br>No excessive corrosion                                                       | 10 cycles                                                                          | MIL-STD-202 Method 106 |
| 5   | Salt spray           | DCR change $\leq \pm 10\%$<br>No excessive corrosion                                                       | 48 hour exposure, 5 % salt solution                                                | MIL-STD-202 Method 101 |
| 6   | Mechanical vibration | DCR change $\leq \pm 10\%$<br>No mechanical damage                                                         | 0.4 inch D.A. or 30 G between 5-3000 Hz                                            | MIL-STD-202 Method 204 |
| 7   | Mechanical shock     | DCR change $\leq \pm 10\%$<br>No mechanical damage                                                         | 1500 G, 0.5 ms, half-sine shocks                                                   | MIL-STD-202 Method 213 |
| 8   | Life                 | No electrical "opens" during testing<br>Voltage drop change shall be less than $\pm 10\%$ of initial value | 75 % rated current for 2000 hours at ambient temperature between +20 °C and +30 °C | Refer to STP document  |

This legal disclaimer applies to purchasers and users of Bourns® products manufactured by or on behalf of Bourns, Inc. and its affiliates (collectively, "Bourns").

Unless otherwise expressly indicated in writing, Bourns® products and data sheets relating thereto are subject to change without notice. Users should check for and obtain the latest relevant information and verify that such information is current and complete before placing orders for Bourns® products.

The characteristics and parameters of a Bourns® product set forth in its data sheet are based on laboratory conditions, and statements regarding the suitability of products for certain "typical" applications are based on Bourns' knowledge of typical requirements in generic applications. Bourns assumes that "typical" applications include failsafe/backup features to address critical risks to users and are designed to allow rework of Bourns® product to avoid scrap of a device solely due to malfunctioning Bourns® product. The characteristics and parameters of a Bourns® product in a user application may vary from the data sheet characteristics and parameters due to (i) the combination of the Bourns® product with other components in the user's application, or (ii) the environment of the user application itself. The characteristics and parameters of a Bourns® product also can and do vary in different applications and actual performance may vary over time. Thus, users should always verify the actual performance of the Bourns® product in their specific devices and applications and make their own independent judgments regarding the suitability of Bourns® product and the amount of additional test margin to design into their device or application to compensate for differences between laboratory and real-world conditions.

Unless Bourns has explicitly designated an individual Bourns® product as meeting the requirements of a particular industry standard (e.g., IATF 16949) or a particular qualification (e.g., UL listed or recognized), Bourns is not responsible for any failure of an individual Bourns® product to meet the requirements of such industry standard or particular qualification even if such industry standard or qualification is a "state of art". Users of Bourns® products are responsible for ensuring compliance with safety-related requirements and standards applicable to their devices or applications.

Bourns® products are not recommended, authorized or intended for use in applications where failure or malfunction may result in personal injury, death, or severe property or environmental damage, such as without limitation nuclear, life-critical medical and certain automotive and aviation applications. Except as set forth in the bullet points below or unless expressly and specifically approved in writing on a case-by-case basis by an authorized Bourns' representative, use of any Bourns® products in such unauthorized high-risk applications is at the user's sole risk.

- Bourns considers implantable/invasive devices and devices/procedures designed as life-supporting or life-sustaining by the U.S. Food and Drug Administration or equivalent organizations outside of the United States as "life-critical" medical applications. Bourns expressly identifies those Bourns® standard products that are suitable for use in typical medical applications that are not life-critical in its publication entitled "Bourns Medical Grade Component Guide."
- Bourns expressly identifies those Bourns® standard products that are suitable for use in typical automotive applications associated with any Automate Safety Integrity Level (ASIL) in its publication entitled "Bourns Automotive Grade Component Guide." Bourns' designation of Bourns® product as compliant with the AEC-Q standard does not by itself mean that Bourns has approved such product for use in an automotive application.
- Bourns expressly identifies Bourns® standard products that are suitable for use in the typical aviation applications/systems requiring System Design Assurance Level (RTCA DO-254 DAL) of C, D or E in its publication entitled "Bourns Civilian Aerospace/Aviation Grade Component Guide." Bourns does not test its products for compliance with United States Federal Aviation Administration standards or any other generally equivalent governmental organization standard applicable to products designed or manufactured for use in aviation applications. Use of Bourns® standard components in aviation applications associated with RTCA DO-254 DAL A or B without proper approval noted above shall be at the user's sole risk.
- Bourns will review and authorize on a case-by-case basis the use of Bourns® standard products which are at least AEC-Q compliant in space-related civil applications (rockets, satellites) with a negotiated cross-waiver and indemnity agreement.

The use and level of testing applicable to Bourns® custom products shall be negotiated on a case-by-case basis by Bourns and the user for which such Bourns® custom products are specially designed. Absent a written agreement between Bourns and the user regarding the use and level of such testing, the above provisions applicable to Bourns® standard products shall also apply to such Bourns® custom products.

Use of Bourns® products or Bourns' technology in military/defense applications must be reviewed with Bourns for compliance with applicable export control laws and embargoes. Users shall not sell, transfer, export or re-export (which includes transfers within a country) any Bourns® products or technology or technical data for use in activities which involve the design, development, production, use or stockpiling of nuclear, chemical or biological weapons or missiles, nor shall they use Bourns® products or technology or technical data in any facility which engages in activities relating to such devices. Further, Bourns® products and Bourns' technology and technical data may not under any circumstance be exported or re-exported to countries subject to international sanctions or embargoes. Bourns® products and technology may not, without prior authorization from Bourns and/or the Government of a country where such product/technology is designed and/or manufactured, be resold, transferred, or re-exported (including within the same country) to any party not eligible to receive commodities, software, and technical data originating in such country.

To the maximum extent permitted by applicable law, Bourns disclaims (i) any and all liability for special, punitive, consequential, incidental or indirect damages or lost revenues or lost profits, and (ii) any and all implied warranties (those not based on parameters specified in Bourns' data sheets and/or specifications), including implied warranties of fitness for particular purpose, non-infringement and merchantability.

*For your convenience, copies of this Legal Disclaimer Notice with German, Spanish, Japanese, Traditional Chinese and Simplified Chinese bilingual versions are available at:*

Web Page: <https://www.bourns.com/legal/disclaimers-terms-and-policies>

PDF: <https://www.bourns.com/docs/Legal/disclaimer.pdf>