

# ANTREX Electronics

Electronic Components Sourcing Information

---

## Product Reference Information

**Part Number:** GBPC25005  
**Manufacturer:** Diodes Incorporated  
**Package:** 4-Square, GBPC  
**Availability:** Please confirm with sales

### Product Page:

<https://antrexco.com/product/details/diodes-incorporated/gbpc25005.html>

### Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

## Contact Information

Email: [info@antrexco.com](mailto:info@antrexco.com)

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

## Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

### Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

---

# GBPC25005/W - GBPC2510/W


## 25A GLASS PASSIVATED BRIDGE RECTIFIER

### Features

- Glass Passivated Die Construction
- Low Reverse Leakage Current
- Low Power Loss, High Efficiency
- Surge Overload Rating to 300A Peak
- Metal Base for Maximum Heat Dissipation
- Case to Terminal Isolation Voltage 1500V
- UL Listed Under Recognized Component Index, File Number E94661
- **Lead Free Finish, RoHS Compliant (Note 4)**

### Mechanical Data

- Case: GBPC / GBPC-W
- Case Material: Molded Plastic with Heatsink Internally Mounted in the Bridge Encapsulation. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminals: Finish — Silver. Plated Leads Solderable per MIL-STD-202, Method 208 (e3)
- Polarity: As Marked on Case
- Mounting: Through Hole for #10 Screw
- Mounting Torque: 8.0 Inch-pounds Maximum
- Ordering Information: See Page 3
- Marking: Type Number
- GBPC Weight: 20 grams (approximate)
- GBPC-W Weight: 14 grams (approximate)



| GBPC / GBPC-W        |                    |       |
|----------------------|--------------------|-------|
| Dim                  | Min                | Max   |
| A                    | 28.30              | 28.80 |
| B                    | 7.40               | 8.25  |
| C                    | 16.10              | 17.10 |
| E                    | 18.80              | 21.30 |
| G                    | 13.80              | 14.80 |
| H                    | Hole for #10 screw |       |
|                      | 5.08Ø              | 5.59Ø |
| J                    | 17.60              | 18.60 |
| K                    | 10.90              | 11.90 |
| L                    | 0.97Ø              | 1.07Ø |
| M                    | 31.80              | —     |
| P                    | 17.60              | 18.60 |
| All Dimensions in mm |                    |       |

"W" Suffix Designates Wire Leads  
 No Suffix Designates Faston Terminals

### Maximum Ratings and Electrical Characteristics

@T<sub>A</sub> = 25°C unless otherwise specified

Single phase, half wave, 60Hz, resistive or inductive load.  
 For capacitive load, derate current by 20%.

| Characteristic                                                                                         | Symbol                            | GBPC25<br>005/W | GBPC25<br>01/W | GBPC25<br>02/W | GBPC25<br>04/W | GBPC25<br>06/W | GBPC25<br>08/W | GBPC25<br>10/W | Unit             |
|--------------------------------------------------------------------------------------------------------|-----------------------------------|-----------------|----------------|----------------|----------------|----------------|----------------|----------------|------------------|
| Peak Repetitive Reverse Voltage                                                                        | V <sub>RRM</sub>                  | 50              | 100            | 200            | 400            | 600            | 800            | 1000           | V                |
| Working Peak Reverse Voltage                                                                           | V <sub>RWM</sub>                  |                 |                |                |                |                |                |                |                  |
| DC Blocking Voltage                                                                                    | V <sub>R</sub>                    |                 |                |                |                |                |                |                |                  |
| RMS Reverse Voltage                                                                                    | V <sub>R(RMS)</sub>               | 35              | 70             | 140            | 280            | 420            | 560            | 700            | V                |
| Average Rectified Output Current @ T <sub>C</sub> = 60°C                                               | I <sub>O</sub>                    | 25              |                |                |                |                |                |                | A                |
| Non-Repetitive Peak Forward Surge Current<br>8.3ms Single Half Sine-Wave Superimposed on<br>Rated Load | I <sub>FSM</sub>                  | 300             |                |                |                |                |                |                | A                |
| Forward Voltage (per element) @ I <sub>F</sub> = 12.5A                                                 | V <sub>FM</sub>                   | 1.1             |                |                |                |                |                |                | V                |
| Peak Reverse Current @ T <sub>C</sub> = 25°C                                                           | I <sub>R</sub>                    | 5.0             |                |                |                |                |                |                | µA               |
| at Rated DC Blocking Voltage @ T <sub>C</sub> = 125°C                                                  |                                   | 500             |                |                |                |                |                |                |                  |
| I <sup>2</sup> t Rating for Fusing (Note 1)                                                            | I <sup>2</sup> t                  | 374             |                |                |                |                |                |                | A <sup>2</sup> s |
| Typical Total Capacitance (Note 2)                                                                     | C <sub>T</sub>                    | 300             |                |                |                |                |                |                | pF               |
| Typical Thermal Resistance per Leg (Note 3)                                                            | R <sub>θJC</sub>                  | 1.3             |                |                |                |                |                |                | °C/W             |
| Operating and Storage Temperature Range                                                                | T <sub>J</sub> , T <sub>STG</sub> | -65 to +150     |                |                |                |                |                |                | °C               |

- Notes:
1. Non-repetitive, for t > 1.0ms and t < 8.3ms.
  2. Measured at 1.0MHz and applied reverse voltage of 4.0V DC.
  3. Thermal resistance junction to case mounted on heatsink.
  4. RoHS revision 13.2.2003. Glass and high temperature solder exemptions applied, see EU Directive Annex Notes 5 and 7.




Fig. 1 Forward Current Derating Curve




Fig. 2 Typical Forward Characteristics (per element)




Fig. 3 Max Non-Repetitive Surge Current




Fig. 4 Typical Total Capacitance (per element)




Fig. 5 Typical Reverse Characteristics (per element)

## Ordering Information (Note 5)

| Device     | Packaging | Shipping |
|------------|-----------|----------|
| GBPC25005  | GBPC      | 100/Tray |
| GBPC2501   | GBPC      | 100/Tray |
| GBPC2502   | GBPC      | 100/Tray |
| GBPC2504   | GBPC      | 100/Tray |
| GBPC2506   | GBPC      | 100/Tray |
| GBPC2508   | GBPC      | 100/Tray |
| GBPC2510   | GBPC      | 100/Tray |
| GBPC25005W | GBPC-W    | 100/Tray |
| GBPC2501W  | GBPC-W    | 100/Tray |
| GBPC2502W  | GBPC-W    | 100/Tray |
| GBPC2504W  | GBPC-W    | 100/Tray |
| GBPC2506W  | GBPC-W    | 100/Tray |
| GBPC2508W  | GBPC-W    | 100/Tray |
| GBPC2510W  | GBPC-W    | 100/Tray |

Note: 5. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02008.pdf>.

### IMPORTANT NOTICE

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes Incorporated.

### LIFE SUPPORT

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

A. Life support devices or systems are devices or systems which:

1. are intended to implant into the body, or
2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.

B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2013, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)