

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: PI6C49X0206TLIEX
Manufacturer: Diodes Incorporated
Package: 14-TSSOP (0.173" , 4.40mm Width)
Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/diodes-incorporated/pi6c49x0206tliex.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.


PI6C49X0206T

Low Skew, 1-To-6 LVCMOS / LVTTTL Fanout Buffer

Description

The PI6C49X0206T is a low skew, 1-to-6 LVCMOS/LVTTTL High Performance Fanout Buffer. The PI6C49X0206T has a single ended clock input. The single ended clock input accepts LVCMOS or LVTTTL input levels. The PI6C49X0206T features a pair of LVCMOS/LVTTTL outputs. Guaranteed output and part-to-part skew characteristics make the PI6C49X0206T ideal for clock distribution applications demanding well defined performance and repeatability.

Block Diagram



Features


- 6 LVCMOS / LVTTTL Outputs
- LVCMOS / LVTTTL Clock Input accepts LVCMOS or LVTTTL Input Levels
- Maximum Output Frequency: 250MHz
- Part-to-Part Skew: 250ps (typical)
- Full 3.3V, 2.5V, 1.8V Operation Mode, or 3.3V/ 2.5V/ 1.8V core with 2.5V, 1.8V, 1.5V Supply Modes
- Ambient Operating Temperature: -40°C to 85°C
- Packaging (Pb-free & Green available):
 - 14-pin, 173-mil wide TSSOP (L)
- Totally Lead-Free & Fully RoHS Compliant (Notes 1 & 2)
- Halogen and Antimony Free. "Green" Device (Note 3)
- For automotive applications requiring specific change control (i.e. parts qualified to AEC-Q100/101/104/200, PPAP capable, and manufactured in IATF 16949 certified facilities), please [contact us](https://www.diodes.com/quality/product-definitions/) or your local Diodes representative.

<https://www.diodes.com/quality/product-definitions/>

Notes:

1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See <https://www.diodes.com/quality/lead-free/> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

Pin Configuration



Pin Description

Pin Number	Pin Name	Type		Pin Description
1	CLK	Input	Pulldown	LVC MOS / LVTTTL clock input.
2	OE	Input		Output Enable pin
3, 6, 9, 11, 13, 14	Q0, Q4, Q5, Q2, Q3, Q1	Output		Single clock output. LVC MOS / LVTTTL interface levels.
4, 7, 10	GND	Power		Power supply ground.
5	VDD	Power		Core supply pins.
8, 12	VDDO	Power		Output supply pins.

Note: Pulldown refer to internal input resistors, typical values in Pin Characteristics table.

Table 1. Pin Characteristics

Symbol	Parameter	Min.	Typ.	Max.	Units
C_N	Capacitance		4		pF
$R_{PULLDOWN}$	Input Pulldown Resistor		51		k Ω

Table 2. Output Logic

Inputs		Output
CLK	OE	Qn
X	L	L
L	H	L
H	H	H

Maximum Ratings

(Above which useful life may be impaired. For user guidelines, not tested.)

Maximum Supply Voltage, VDD, VDDO	4.6V
Inputs, V _I	-0.5V to VDD +0.5V
Output, V _O	-0.5V to VDDO +0.5V
Storage Temperature	-65°C to 150°C
ESD Protection (HBM)	2000V

Note:

Stresses greater than those listed under MAXIMUM RATINGS may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions above those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect reliability.

Power Supply DC Characteristics

T_A = -40°C to 85°C

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
VDD	Core Supply Voltage	3.3V Operation	3.135	3.3	3.465	V
		2.5V Operation	2.375	2.5	2.625	
		1.8V Operation	1.6	1.8	2.0	
VDDO	Output Power Supply Voltage	3.3V Supply	3.135	3.3	3.465	V
		2.5V Supply	2.375	2.5	2.625	
		1.8V Supply	1.6	1.8	2.0	
		1.5V Supply	1.425	1.5	1.575	
IDD	Power Supply Current	No load			2	mA
IDDO	Output Supply Current	5pF load, 25MHz, VDDO = 3.3V		6	9.5	mA
		5pF load, 25MHz, VDDO = 2.5V		5.7	7.2	mA
		5pF load, 25MHz, VDDO = 1.8V		4.5	5.5	mA
		5pF load, 25MHz, VDDO = 1.5V		3.5	4.6	mA
		5pF load, 200MHz, VDDO = 3.3V		57	72	mA
		5pF load, 200MHz, VDDO = 2.5V		44	54	mA
		5pF load, 200MHz, VDDO = 1.8V		32	39	mA
		5pF load, 200MHz, VDDO = 1.5V		19	24	mA

LVC MOS / LV TTL DC Characteristics

T_A = -45°C to 85°C

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
V _{IH}	Input High Voltage	VDD = 3.3V	2		VDD+0.3	V
		VDD = 2.5V	1.7		VDD+0.3	
		VDD = 1.8V	0.65*VDD		VDD+0.3	
V _{IL}	Input Low Voltage	VDD = 3.3V	-0.3		0.8	V
		VDD = 2.5V	-0.3		0.8	
		VDD = 1.8V	-0.3		0.35*VDD	

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
I _{IH}	Input High Current	VDD = V _{IN} = 3.465V			150	μA
		VDD = V _{IN} = 2.625V			150	
		VDD = V _{IN} = 2.0V			150	
I _{IL}	Input Low Current	VDD = 3.465V, V _{IN} = 0	-5			μA
		VDD = 2.625V, V _{IN} = 0	-5			
		VDD = 2.0V, V _{IN} = 0	-5			
V _{OH}	Output High Voltage	VDDO = 3.3V	50Ω to VDDO / 2	2.6		V
			I _{OH} = -100μA	2.9		V
		VDDO = 2.5V	50Ω to VDDO / 2	1.8		V
			I _{OH} = -100μA	2.2		V
		VDDO = 1.8V	50Ω to VDDO / 2	1.2		V
			I _{OH} = -100μA	1.6		V
		VDDO = 1.5V	50Ω to VDDO / 2	0.96		V
			I _{OH} = -100μA	1.3		V
V _{OL}	Output Low Voltage	VDDO = 3.3V	50Ω to VDDO / 2		0.6	V
			I _{OL} = 100μA		0.2	V
		VDDO = 2.5V	50Ω to VDDO / 2		0.6	V
			I _{OL} = 100μA		0.2	V
		VDDO = 1.8V	50Ω to VDDO / 2		0.6	V
			I _{OL} = 100μA		0.2	V
		VDDO = 1.5V	50Ω to VDDO / 2		0.6	V
			I _{OL} = 100μA		0.2	V

AC Characteristics

VDD = 3.3V ± 5%, T_A = -45°C to 85°C

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
f _{MAX}	Output Frequency	VDDO = 3.3V			250	MHz
		VDDO = 2.5V			250	
		VDDO = 1.8V			250	
		VDDO = 1.5V			250	
tp _{LH}	Propagation Delay, Low-to-High ⁽¹⁾	VDDO = 3.3V, f ≤ 250MHz	1.2	1.6	2.8	ns
		VDDO = 2.5V, f ≤ 250MHz	1.45	1.9	3.3	
		VDDO = 1.8V, f ≤ 250MHz	2.2	2.8	3.6	
		VDDO = 1.5V, f ≤ 250MHz	3.25	4	4.7	
tsk(o)	Output Skew ⁽²⁾	VDDO = 2.5V, 3.3V		68	100	ps
		VDDO = 1.5V, 1.8V		80	150	ps
tsk(pp)	Part-to-Part Skew ⁽³⁾			250	800	ps

PI6C49X0206T

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
t_R	Output Rise Time ⁽⁴⁾	VDDO = 3.3V	300		800	ps
		VDDO = 2.5V	300		800	
		VDDO = 1.8V	300		800	
		VDDO = 1.5V	600		1000	
t_F	Output Fall Time ⁽⁴⁾	VDDO = 3.3V	300		800	ps
		VDDO = 2.5V	300		800	
		VDDO = 1.8V	300		800	
		VDDO = 1.5V	600		1000	
odc	Output Duty Cycle	$f \leq 133\text{MHz}$	45		55	%
		$133\text{MHz} < f \leq 250\text{MHz}$	40		60	%
t_{jit}	Additive RMS Jitter	156.25MHz (@12kHz to 20MHz)		0.03		ps
		125MHz (@12kHz to 20MHz)		0.05		ps
t_{OED}	Output Disable Time				6	ns
t_{OE}	Output Enable Time				6	ns

Parameters measured at f_{MAX} unless otherwise noted.

NOTE:

1. Measured from VDD /2 of the input to VDDO /2 of the output.
2. Defined as skew between outputs at the same supply voltage and with equal load conditions. Measured at VDDO /2.
3. Defined as skew between outputs on different devices operating at the same supply voltages and with equal load conditions. Using the same type of inputs on each device, the outputs are measured at VDDO /2.
4. Defined from 20% to 80%

VDD = 2.5V $\pm$ 5%, T_A = -45°C to 85°C

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
f_{MAX}	Output Frequency	VDDO = 2.5V			250	MHz
		VDDO = 1.8V			250	
		VDDO = 1.5V			250	
t_{PLH}	Propagation Delay, Low-to-High ⁽¹⁾	VDDO = 2.5V, $f \leq 250\text{MHz}$	1.56	2	2.7	ns
		VDDO = 1.8V, $f \leq 250\text{MHz}$	2.3	2.9	3.7	
		VDDO = 1.5V, $f \leq 250\text{MHz}$	3.34	4	4.83	
$tsk(o)$	Output Skew ⁽²⁾	VDDO = 1.8V, 2.5V		68	100	ps
		VDDO = 1.5V		80	150	ps
$tsk(pp)$	Part-to-Part Skew ⁽³⁾			250	800	ps
t_R	Output Rise Time ⁽⁴⁾	VDDO = 2.5V	300		800	ps
		VDDO = 1.8V	300		800	
		VDDO = 1.5V	500		1000	
t_F	Output Fall Time ⁽⁴⁾	VDDO = 2.5V	300		800	ps
		VDDO = 1.8V	300		800	
		VDDO = 1.5V	500		1000	

PI6C49X0206T

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
odc	Output Duty Cycle	$f \leq 133\text{MHz}$	45		55	%
		$133\text{MHz} < f \leq 250\text{MHz}$	40		60	%
t_{jit}	Additive RMS Jitter	156.25MHz (@12kHz to 20MHz)		0.03		ps
		125MHz (@12kHz to 20MHz)		0.05		ps
t_{OED}	Output Disable Time				10	ns
t_{OE}	Output Enable Time				10	ns

Parameters measured at f_{MAX} unless otherwise noted.

NOTE:

1. Measured from VDD /2 of the input to VDDO /2 of the output.
2. Defined as skew between outputs at the same supply voltage and with equal load conditions. Measured at VDDO /2.
3. Defined as skew between outputs on different devices operating at the same supply voltages and with equal load conditions. Using the same type of inputs on each device, the outputs are measured at VDDO /2.
4. Defined from 20% to 80%

VDD = 1.8V $\pm$ 0.2V, $T_A = -45^\circ\text{C}$ to 85°C

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Units
f_{MAX}	Output Frequency	VDDO = 1.8V			250	MHz
		VDDO = 1.5V			250	
t_{PLH}	Propagation Delay, Low-to-High ⁽¹⁾	VDDO = 1.8V, $f \leq 250\text{MHz}$	2.57	3.25	4	ns
		VDDO = 1.5V, $f \leq 250\text{MHz}$	3.57	4.3	5.1	
$tsk(o)$	Output Skew ⁽²⁾	VDDO = 1.8V		68	100	ps
		VDDO = 1.5V		80	150	ps
$tsk(pp)$	Part-to-Part Skew ⁽³⁾			250	800	ps
t_R	Output Rise Time ⁽⁴⁾	VDDO = 1.8V	300		800	ps
		VDDO = 1.5V	500		1000	
t_F	Output Fall Time ⁽⁴⁾	VDDO = 1.8V	300		800	ps
		VDDO = 1.5V	500		1000	
odc	Output Duty Cycle	$f \leq 133\text{MHz}$	45		55	%
		$133\text{MHz} < f \leq 250\text{MHz}$	40		60	%
t_{jit}	Additive RMS Jitter	156.25MHz (@12kHz to 20MHz)		0.03		ps
		125MHz (@12kHz to 20MHz)		0.06		ps
t_{OED}	Output Disable Time				14	ns
t_{OE}	Output Enable Time				14	ns


Parameters measured at f_{MAX} unless otherwise noted.

NOTE:

1. Measured from VDD /2 of the input to VDDO /2 of the output.
2. Defined as skew between outputs at the same supply voltage and with equal load conditions. Measured at VDDO /2.
3. Defined as skew between outputs on different devices operating at the same supply voltages and with equal load conditions. Using the same type of inputs on each device, the outputs are measured at VDDO /2.
4. Defined from 20% to 80%

PI6C49X0206T


Part Marking



*: Die Rev
Y: Date Code (Year)
W: Date Code (Workweek)
1st X: Assembly Code
2nd X: Fab Code
Note: Date Code per MA-1251

Packaging Mechanical

14-TSSOP (L)



16-0060

For latest package info.

please check: <http://www.diodes.com/design/support/packaging/pericom-packaging/packaging-mechanicals-and-thermal-characteristics/>

Mechanical Data

Mechanical Data is not available at this time. To obtain advance information regarding the Mechanical Data, please contact your local sales representative.

Ordering Information

Orderable Part Number	Package Code	Package Description
PI6C49X0206TLIEX	L	14-pin, 173mil Wide (TSSOP)

Notes:

1. No purposely added lead. Fully EU Directive 2002/95/EC (RoHS), 2011/65/EU (RoHS 2) & 2015/863/EU (RoHS 3) compliant.
2. See <https://www.diodes.com/quality/lead-free/> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.
4. I = Industrial
5. E = Pb-free and Green
6. X suffix = Tape/Reel

IMPORTANT NOTICE

1. DIODES INCORPORATED (Diodes) AND ITS SUBSIDIARIES MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO ANY INFORMATION CONTAINED IN THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

2. The Information contained herein is for informational purpose only and is provided only to illustrate the operation of Diodes' products described herein and application examples. Diodes does not assume any liability arising out of the application or use of this document or any product described herein. This document is intended for skilled and technically trained engineering customers and users who design with Diodes' products. Diodes' products may be used to facilitate safety-related applications; however, in all instances customers and users are responsible for (a) selecting the appropriate Diodes products for their applications, (b) evaluating the suitability of Diodes' products for their intended applications, (c) ensuring their applications, which incorporate Diodes' products, comply the applicable legal and regulatory requirements as well as safety and functional-safety related standards, and (d) ensuring they design with appropriate safeguards (including testing, validation, quality control techniques, redundancy, malfunction prevention, and appropriate treatment for aging degradation) to minimize the risks associated with their applications.

3. Diodes assumes no liability for any application-related information, support, assistance or feedback that may be provided by Diodes from time to time. Any customer or user of this document or products described herein will assume all risks and liabilities associated with such use, and will hold Diodes and all companies whose products are represented herein or on Diodes' websites, harmless against all damages and liabilities.

4. Products described herein may be covered by one or more United States, international or foreign patents and pending patent applications. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks and trademark applications. Diodes does not convey any license under any of its intellectual property rights or the rights of any third parties (including third parties whose products and services may be described in this document or on Diodes' website) under this document.

5. Diodes' products are provided subject to Diodes' Standard Terms and Conditions of Sale (<https://www.diodes.com/about/company/terms-and-conditions/terms-and-conditions-of-sales/>) or other applicable terms. This document does not alter or expand the applicable warranties provided by Diodes. Diodes does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel.

6. Diodes' products and technology may not be used for or incorporated into any products or systems whose manufacture, use or sale is prohibited under any applicable laws and regulations. Should customers or users use Diodes' products in contravention of any applicable laws or regulations, or for any unintended or unauthorized application, customers and users will (a) be solely responsible for any damages, losses or penalties arising in connection therewith or as a result thereof, and (b) indemnify and hold Diodes and its representatives and agents harmless against any and all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim relating to any noncompliance with the applicable laws and regulations, as well as any unintended or unauthorized application.

7. While efforts have been made to ensure the information contained in this document is accurate, complete and current, it may contain technical inaccuracies, omissions and typographical errors. Diodes does not warrant that information contained in this document is error-free and Diodes is under no obligation to update or otherwise correct this information. Notwithstanding the foregoing, Diodes reserves the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. This document is written in English but may be translated into multiple languages for reference. Only the English version of this document is the final and determinative format released by Diodes.

8. Any unauthorized copying, modification, distribution, transmission, display or other use of this document (or any portion hereof) is prohibited. Diodes assumes no responsibility for any losses incurred by the customers or users or any third parties arising from any such unauthorized use.

9. This Notice may be periodically updated with the most recent version available at <https://www.diodes.com/about/company/terms-and-conditions/important-notice>

The Diodes logo is a registered trademark of Diodes Incorporated in the United States and other countries.

All other trademarks are the property of their respective owners.

© 2026 Diodes Incorporated. All Rights Reserved.

www.diodes.com