

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: PTSAHT120630V035

Manufacturer: Eaton - Electronics Division

Package: 1206 (3216 Metric), Concave

Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/eaton-electronics-division/ptsah120630v035.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

PTSAHT1206

Automotive high temperature SMD PTC fuses



Applications

- Infotainment
- In-vehicle navigation
- Telematics
- Car lighting
- Power window and seat control
- Instrument clusters
- PCB trace protection

Environmental compliance



Product features

- AEC-Q200 qualified
- Positive temperature coefficient (PTC)
- Surface mount resettable fuse
- Compact 1206 (3216 metric) footprint
- High temperature
- Voltage rating 16 V to 30 V
- Current rating from 0.16 A to 0.50 A
- Fast time-to-trip

Part number system/ordering:

PTSAHT120630V016

- PT= PTC resettable fuse
- S= Surface mount
- AHT= Automotive with high operating temperature
- 1206= Dimension code
- 30V= Maximum voltage
- 016= Ihold current rating (016= 0.16 A)


Product specifications

	V _{max} ¹	I _{max} ²	I _{hold} ³	I _{trip} ⁴	P _d ⁵	Time-to-trip (maximum)		Resistance ⁶		
Part number	(V _{dc})	(A)	(A)	(A)	typical (W)	(A)	(seconds)	Initial (R _i) minimum (Ω)	Post trip (R _p) maximum (Ω)	Part marking
PTSAHT120630V016	30	20	0.16	0.80	0.90	8.00	0.10	0.70	6.00	01H
PTSAHT120616V035	16	50	0.35	0.95	1.00	3.50	0.20	0.20	1.60	03H
PTSAHT120630V035	30	20	0.35	1.75	1.20	8.00	0.10	0.20	2.20	03H
PTSAHT120624V050	24	20	0.50	2.50	1.70	8.00	0.10	0.20	1.60	05H


1. V_{max}: Maximum continuous voltage the device can withstand without damage at rated current
2. I_{max}: Maximum fault current the device can withstand without damage at rated voltage
3. I_{hold}: Maximum current the device will pass without interruption at +23 °C still air
4. I_{trip}: Minimum current that will transition the device from low resistance to high resistance at +23 °C still air
5. P_d: Power dissipated from the device when in tripped state at +23 °C still air

6. R_i: Minimum resistance of the device at +23 °C
R_p: Maximum resistance of the device one hour after tripping at +23 °C

Dimensions—mm



Recommended pad layout



Part number	A typ	A max	B typ	B max	C typ	C max	D min	E min	F	G	H
PTSAHT120630V016	3.35	3.50	1.70	1.80	0.60	0.89	0.25	0.076	1.8	1.0	1.8
PTSAHT120616V035	3.35	3.50	1.70	1.80	0.65	1.14	0.25	0.076	1.8	1.0	1.8
PTSAHT120630V035	3.35	3.50	1.70	1.80	1.05	1.46	0.25	0.076	1.8	1.0	1.8
PTSAHT120624V050	3.35	3.50	1.70	1.80	1.05	1.46	0.25	0.076	1.8	1.0	1.8

Thermal derating chart - I_{hold} (A)

Part number	Maximum ambient temperature (°C)									
	-40	-20	0	25	40	50	60	70	85	125
PTSAHT120630V016	0.25	0.21	0.19	0.16	0.14	0.13	0.12	0.11	0.09	0.05
PTSAHT120616V035	0.54	0.48	0.43	0.35	0.32	0.29	0.26	0.24	0.20	0.10
PTSAHT120630V035	0.51	0.46	0.41	0.35	0.31	0.29	0.26	0.24	0.20	0.10
PTSAHT120624V050	0.73	0.66	0.58	0.50	0.45	0.42	0.39	0.35	0.31	0.17

General specifications

Operating temperature: -40 °C to + 125 °C (with derating)

Storage temperature: -10 °C to + 40 °C

Storage relative humidity: ≤70%

Storage condition: Keep away from corrosive atmosphere and sunlight

Passive aging: IEC60738-1, +60 °C, 1000 hours, ± ≤ 20%
IEC60738-1, +85 °C, 1000 hours, ± ≤ 20%

Humidity aging: +85 °C, 85% RH, 100 hours, ± ≤ 20%

Thermal shock: IEC60738-1, +125 °C/ -40 °C, 20 cycles, ≤ 50%

Trip cycle life: UL1434, Vmax, Imax, 100 cycles, no arcing or burning

Trip endurance: UL1434, Vmax, Itrip ≤ I ≤ Imax, 2 hours, no arcing or burning

MSL test: J-STD-020, MSL=1, pass and no visible damage


Packaging information

PTSAHT120616V035, PTSAHT120630V016

Supplied in tape and reel packaging, 4000 parts per 7.0" (178 mm) diameter reel (EIA-481 compliant)

PTSAHT120624V050, PTSAHT120630V035

Supplied in tape and reel packaging, 3000 parts per 7.0" (178 mm) diameter reel (EIA-481 compliant)



W	F	E1	E2	P0	P1	P2	D0	D1	A0	B0	K0	T
8.00 ± 0.30	3.50 ± 0.10	1.75 ± 0.10	-	4.00 ± 0.10	4.00 ± 0.10	2.00 ± 0.05	1.55 ± 0.10/-0	-	1.77 ± 0.10	3.40 ± 0.10	1.04 ± 0.10	0.22 ± 0.05

Solder reflow profile




Table 1 - Standard SnPb solder (T_c)

Package thickness	Volume mm ³ <350	Volume mm ³ ≥350
<2.5 mm)	235 °C	220 °C
≥2.5 mm	220 °C	220 °C

Table 2 - Lead (Pb) Free Solder (T_c)

Package thickness	Volume mm ³ <350	Volume mm ³ 350 - 2000	Volume mm ³ >2000
<1.6 mm	260 °C	260 °C	260 °C
1.6 – 2.5 mm	260 °C	250 °C	245 °C
>2.5 mm	250 °C	245 °C	245 °C

Reference J-STD-020

Profile feature	Standard SnPb solder	Lead (Pb) free solder
Preheat and soak		
• Temperature min. (T_{smin})	100 °C	150 °C
• Temperature max. (T_{smax})	150 °C	200 °C
• Time (T_{smin} to T_{smax}) (t_s)	60-120 seconds	60-120 seconds
Ramp up rate T_L to T_p	3 °C/ second max.	3 °C/ second max.
Liquidous temperature (T_L)	183 °C	217 °C
Time (t_L) maintained above T_L	60-150 seconds	60-150 seconds
Peak package body temperature (T_p)*	Table 1	Table 2
Time (t_p)* within 5 °C of the specified classification temperature (T_c)	20 seconds*	30 seconds*
Ramp-down rate (T_p to T_L)	6 °C/ second max.	6 °C/ second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

* Tolerance for peak profile temperature (T_p) is defined as a supplier minimum and a user maximum.

Life Support Policy: Eaton does not authorize the use of any of its products for use in life support devices or systems without the express written approval of an officer of the Company. Life support systems are devices which support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

Eaton reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Eaton also reserves the right to change or update, without notice, any technical information contained in this bulletin.

Eaton
Electronics Division
1000 Eaton Boulevard
Cleveland, OH 44122
United States
Eaton.com/electronics

© 2021 Eaton
All Rights Reserved
Printed in USA
Publication No. ELX1045 BU-ELX21045
June 2021

Eaton is a registered trademark.

All other trademarks are property of their respective owners.

Follow us on social media to get the latest product and support information.

