

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: AIKQ120N75CP2XKSA1

Manufacturer: Infineon Technologies

Package: TO-247-3

Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/infineon-technologies/aikq120n75cp2xksa1.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

Final datasheet

Short circuit rugged 750 V EDT2 IGBT co-packed with fast soft recovery diode

Features

- $V_{CE} = 750\text{ V}$
- $I_C = 120\text{ A}$
- 750 V collector-emitter blocking voltage capability
- Suitable for 470 V V_{DC} systems and increase overvoltage margin for 400 V V_{DC} systems
- Very low $V_{CEsat} = 1.3\text{ V}$ (typ.) at $I_{Cnom} = 120\text{ A}$, 25°C
- Short circuit robust $t_{sc} = 5\text{ }\mu\text{s}$ at $V_{CE} = 470\text{ V}$, $V_{GE} = 15\text{ V}$
- Self limiting current under short circuit condition
- Positive thermal coefficient and very tight parameter distribution for easy paralleling
- Drop-in replacement for previous generation devices $I_C = 120\text{ A}$, $T_c = 100^\circ\text{C}$
- Excellent current sharing in parallel operation
- Smooth switching characteristics, low EMI signature
- Low gate charge Q_G
- Simple gate drive design
- Co-packed with fast soft recovery emitter controlled 3 diode
- TO247PLUS package with high creepage distance
- High reliability

Potential applications

- xEV traction inverter
- DC-link discharge switch
- Automotive aux-drives


Product validation

- Qualified for automotive applications
- Qualified according to AEC-Q101

Description

Package pin definition:

- Pin C & backside - collector
- Pin E - emitter
- Pin G - gate



Halogen-free




RoHS



Lead-free



Green



Type	Package	Marking
AIKQ120N75CP2	PG-TO247-3-U01	AKQ12FCP



Table of contents

	Description	1
	Features	1
	Potential applications	1
	Product validation	1
	Table of contents	2
1	Package	3
2	IGBT	3
3	Diode	5
4	Characteristics diagrams	7
5	Package outlines	14
	Revision history	15
	Disclaimer	16

1 Package

Table 1 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Internal emitter inductance measured 5 mm (0.197 in.) from case	L_E			13		nH
Storage temperature	T_{stg}		-55		150	°C
Soldering temperature	T_{sold}	Wave soldering 1.6 mm (0.063 in.) from case for 10 s			260	°C
Thermal resistance, junction-ambient	$R_{th(j-a)}$				40	K/W
IGBT thermal resistance, junction-case	$R_{th(j-c)}$			0.17	0.22	K/W
Diode thermal resistance, junction-case	$R_{th(j-c)}$			0.31	0.4	K/W

2 IGBT

Table 2 Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Collector-emitter voltage	V_{CE}			750	V
DC collector current, limited by T_{vjmax}	I_C		$T_c = 25\text{ °C}$	150	A
			$T_c = 100\text{ °C}$	120	
Pulsed collector current, t_p limited by T_{vjmax}	I_{Cpulse}			360	A
Turn-off safe operating area		$V_{CE} \leq 750\text{ V}$, $t_p = 1\text{ }\mu\text{s}$, $T_{vj} \leq 175\text{ °C}$		360	A
Gate-emitter voltage	V_{GE}			± 20	V
Transient gate-emitter voltage	V_{GE}	$t_p < 0.1\text{ }\mu\text{s}$, $D < 0.01$		± 30	V
Short-circuit withstand time	t_{SC}	$V_{CC} \leq 470\text{ V}$, $V_{GE} = 15\text{ V}$, Allowed number of short circuits < 1000 , Time between short circuits $\geq 1.0\text{ s}$, $T_{vj} = 25\text{ °C}$		5	μs
Power dissipation	P_{tot}		$T_c = 25\text{ °C}$	682	W
			$T_c = 100\text{ °C}$	341	

Table 3 **Characteristic values**

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	V_{CEsat}	$I_C = 120 \text{ A}$, $V_{GE}=15 \text{ V}$	$T_{vj} = 25 \text{ }^{\circ}\text{C}$	1.2	1.3	1.5	V
			$T_{vj} = 175 \text{ }^{\circ}\text{C}$		1.53		
Gate-emitter threshold voltage	V_{GETh}	$I_C = 1.6 \text{ mA}$, $V_{CE} = V_{GE}$		5.2	5.8	6.4	V
Zero gate-voltage collector current	I_{CES}	$V_{CE} = 750 \text{ V}$, $V_{GE}=0 \text{ V}$	$T_{vj}=25 \text{ }^{\circ}\text{C}$			200	μA
			$T_{vj}=175 \text{ }^{\circ}\text{C}$		4000		
Gate-emitter leakage current	I_{GES}	$V_{CE}=0 \text{ V}$, $V_{GE}=20 \text{ V}$				100	nA
Transconductance	g_{fs}	$I_C = 120 \text{ A}$, $V_{CE}=20 \text{ V}$			90		S
Short-circuit collector current	I_{SC}	$V_{CC} \leq 470 \text{ V}$, $V_{GE}=15 \text{ V}$, $t_{SC} \leq 5 \text{ } \mu\text{s}$, Allowed number of short circuits < 1000, Time between short circuits $\geq 1.0 \text{ s}$, $T_{vj}=25 \text{ }^{\circ}\text{C}$	$T_{vj} = 25 \text{ }^{\circ}\text{C}$		750		A
Input capacitance	C_{ies}	$V_{CE}=25 \text{ V}$, $V_{GE}=0 \text{ V}$, $f=100 \text{ kHz}$			13100		pF
Output capacitance	C_{oes}	$V_{CE}=25 \text{ V}$, $V_{GE}=0 \text{ V}$, $f=100 \text{ kHz}$			337		pF
Reverse transfer capacitance	C_{res}	$V_{CE}=25 \text{ V}$, $V_{GE}=0 \text{ V}$, $f=100 \text{ kHz}$			59		pF
Gate charge	Q_G	$V_{CC} = 600 \text{ V}$, $I_C = 120 \text{ A}$			731		nC
Turn-on delay time	$t_{d(on)}$	$V_{GE} = -8/15 \text{ V}$, $R_{G(on)} = 5 \text{ } \Omega$, $R_{G(off)} = 5 \text{ } \Omega$, $L_{\sigma}=50 \text{ nH}$, $C_{\sigma}=30 \text{ pF}$	$T_{vj} = 25 \text{ }^{\circ}\text{C}$, $I_C = 120 \text{ A}$		71		ns
			$T_{vj} = 175 \text{ }^{\circ}\text{C}$, $I_C = 120 \text{ A}$		50		
Rise time (inductive load)	t_r	$V_{GE} = -8/15 \text{ V}$, $R_{G(on)} = 5 \text{ } \Omega$, $R_{G(off)} = 5 \text{ } \Omega$, $L_{\sigma}=50 \text{ nH}$, $C_{\sigma}=30 \text{ pF}$	$T_{vj} = 25 \text{ }^{\circ}\text{C}$, $I_C = 120 \text{ A}$		69		ns
			$T_{vj} = 175 \text{ }^{\circ}\text{C}$, $I_C = 120 \text{ A}$		68		
Turn-off delay time	$t_{d(off)}$	$V_{GE} = -8/15 \text{ V}$, $R_{G(on)} = 5 \text{ } \Omega$, $R_{G(off)} = 5 \text{ } \Omega$, $L_{\sigma}=50 \text{ nH}$, $C_{\sigma}=30 \text{ pF}$	$T_{vj} = 25 \text{ }^{\circ}\text{C}$, $I_C = 120 \text{ A}$		244		ns
			$T_{vj} = 175 \text{ }^{\circ}\text{C}$, $I_C = 120 \text{ A}$		226		
Fall time (inductive load)	t_f	$V_{GE} = -8/15 \text{ V}$, $R_{G(on)} = 5 \text{ } \Omega$, $R_{G(off)} = 5 \text{ } \Omega$, $L_{\sigma}=50 \text{ nH}$, $C_{\sigma}=30 \text{ pF}$	$T_{vj} = 25 \text{ }^{\circ}\text{C}$, $I_C = 120 \text{ A}$		50.5		ns
			$T_{vj} = 175 \text{ }^{\circ}\text{C}$, $I_C = 120 \text{ A}$		67		

(table continues...)

Table 3 (continued) Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Turn-on energy ¹⁾	E_{on}	$V_{GE} = -8/15\text{ V}$, $R_{G(on)} = 5\ \Omega$, $R_{G(off)} = 5\ \Omega$, $L_{\sigma}=50\text{ nH}$, $C_{\sigma}=30\text{ pF}$	$T_{vj} = 25\text{ }^{\circ}\text{C}$, $I_C = 120\text{ A}$	6.82		mJ
			$T_{vj} = 175\text{ }^{\circ}\text{C}$, $I_C = 120\text{ A}$	7.3		
Turn-off energy	E_{off}	$V_{GE} = -8/15\text{ V}$, $R_{G(on)} = 5\ \Omega$, $R_{G(off)} = 5\ \Omega$, $L_{\sigma}=50\text{ nH}$, $C_{\sigma}=30\text{ pF}$	$T_{vj} = 25\text{ }^{\circ}\text{C}$, $I_C = 120\text{ A}$	3.8		mJ
			$T_{vj} = 175\text{ }^{\circ}\text{C}$, $I_C = 120\text{ A}$	4.7		
Total switching energy	E_{ts}	$V_{GE} = -8/15\text{ V}$, $R_{G(on)} = 5\ \Omega$, $R_{G(off)} = 5\ \Omega$, $L_{\sigma}=50\text{ nH}$, $C_{\sigma}=30\text{ pF}$	$T_{vj} = 25\text{ }^{\circ}\text{C}$, $I_C = 120\text{ A}$	10.3		mJ
			$T_{vj} = 175\text{ }^{\circ}\text{C}$, $I_C = 120\text{ A}$	12.1		
Operating junction temperature	T_{vj}		-40		175	$^{\circ}\text{C}$

1) Includes IGBT losses caused by the reverse recovery current

3 Diode

Table 4 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Diode forward current, limited by T_{vjmax}	I_F	$T_C = 25\text{ }^{\circ}\text{C}$	150	A
		$T_C = 100\text{ }^{\circ}\text{C}$	120	
Diode pulsed current, t_p limited by T_{vjmax}	I_{Fpulse}		360	A
Power dissipation	P_{tot}	$T_C = 25\text{ }^{\circ}\text{C}$	375	W
		$T_C = 100\text{ }^{\circ}\text{C}$	170	

Table 5 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Diode forward voltage	V_F	$I_F = 120\text{ A}$	$T_{vj}=25\text{ }^{\circ}\text{C}$	1.7	1.95	V
			$T_{vj}=175\text{ }^{\circ}\text{C}$	1.74		

(table continues...)

Table 5 (continued) Characteristic values


Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Diode reverse recovery charge	Q_{rr}	$V_R < 470 \text{ V}$, $R_{G(on)}=4.8 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}$, $I_F = 120 \text{ A}$, $-di_F/dt = 1070 \text{ A}/\mu\text{s}$	3.58		μC
			$T_{vj} = 175 \text{ }^\circ\text{C}$, $I_F = 120 \text{ A}$, $-di_F/dt = 1055 \text{ A}/\mu\text{s}$	5.28		
Diode peak reverse recovery current	I_{rrm}	$V_R < 470 \text{ V}$, $R_{G(on)}=4.8 \Omega$	$T_{vj} = 25 \text{ }^\circ\text{C}$, $I_F = 120 \text{ A}$, $-di_F/dt = 1070 \text{ A}/\mu\text{s}$	33		A
			$T_{vj} = 175 \text{ }^\circ\text{C}$, $I_F = 120 \text{ A}$, $-di_F/dt = 1055 \text{ A}/\mu\text{s}$	43		
Reverse recovery energy	E_{rec}	$V_R < 470 \text{ V}$, $V_{GE} = -8/15 \text{ V}$, $R_{G(on)}=4.8 \Omega$, $L_\sigma = 50 \text{ nH}$, $C_\sigma = 30 \text{ pF}$	$T_{vj} = 25 \text{ }^\circ\text{C}$, $I_F = 120 \text{ A}$, $-di_F/dt = 1070 \text{ A}/\mu\text{s}$	1.24		mJ
			$T_{vj} = 175 \text{ }^\circ\text{C}$, $I_F = 120 \text{ A}$, $-di_F/dt = 1055 \text{ A}/\mu\text{s}$	1.61		
Operating junction temperature	T_{vj}		-40		175	$^\circ\text{C}$

4 Characteristics diagrams

Typical output characteristic

$$I_C = f(V_{CE})$$


$$T_{vj} = 175\text{ °C}$$



Power dissipation as a function of case temperature

$$P_{tot} = f(T_c)$$


$$T_{vj} \leq 175\text{ °C}$$



Collector current as a function of case temperature

$$I_C = f(T_c)$$


$$T_{vj} \leq 175\text{ °C}, V_{GE} = 15\text{ V}$$



Typical output characteristic

$$I_C = f(V_{CE})$$

$$T_{vj} = 25\text{ °C}$$




4 Characteristics diagrams

Typical transfer characteristic

$$I_C = f(V_{GE})$$


$$V_{CE} = 20 \text{ V}$$



Typical collector-emitter saturation voltage as a function of junction temperature

$$V_{CEsat} = f(T_{vj})$$


$$V_{GE} = 15 \text{ V}$$



Typical Gate-emitter threshold voltage as a function of junction temperature

$$V_{GEth} = f(T_{vj})$$


$$I_C = 1.60 \text{ mA}$$



Typical switching times as a function of collector current

$$t = f(I_C)$$

$$R_{G(off)} = 5.0 \Omega, V_{CE} = 470 \text{ V}, T_{vj} = 175^\circ\text{C}, V_{GE} = -8/15 \text{ V}, R_{G(on)} = 5 \Omega$$




4 Characteristics diagrams

Typical switching times as a function of gate resistor

$$t = f(R_G)$$


$I_C = 120.0 \text{ A}$, $V_{CE} = 470 \text{ V}$, $T_{vj} = 175 \text{ }^\circ\text{C}$, $V_{GE} = -8/15 \text{ V}$



Typical switching times as a function of junction temperature

$$t = f(T_{vj})$$


$I_C = 120.0 \text{ A}$, $R_{G(off)} = 5.0 \text{ } \Omega$, $V_{CE} = 470 \text{ V}$, $V_{GE} = -8/15 \text{ V}$, $R_{G(on)} = 5 \text{ } \Omega$



Typical switching energy losses as a function of collector current

$$E = f(I_C)$$


$R_{G(off)} = 5.0 \text{ } \Omega$, $V_{CE} = 470 \text{ V}$, $T_{vj} = 175 \text{ }^\circ\text{C}$, $V_{GE} = -8/15 \text{ V}$, $R_{G(on)} = 5 \text{ } \Omega$



Typical switching energy losses as a function of gate resistor

$$E = f(R_G)$$

$I_C = 120.0 \text{ A}$, $V_{CE} = 470 \text{ V}$, $T_{vj} = 175 \text{ }^\circ\text{C}$, $V_{GE} = -8/15 \text{ V}$




4 Characteristics diagrams

Typical switching energy losses as a function of junction temperature

$$E = f(T_{vj})$$


$I_C = 120.0 \text{ A}$, $R_{G(off)} = 5.0 \text{ } \Omega$, $V_{CE} = 470 \text{ V}$, $V_{GE} = -8/15 \text{ V}$, $R_{G(on)} = 5 \text{ } \Omega$



Typical switching energy losses as a function of collector emitter voltage

$$E = f(V_{CE})$$


$I_C = 120 \text{ A}$, $R_{G(off)} = 5 \text{ } \Omega$, $T_{vj} \leq 175 \text{ }^\circ\text{C}$, $V_{GE} = -8/15 \text{ V}$, $R_{G(on)} = 5 \text{ } \Omega$



Typical gate charge

$$V_{GE} = f(Q_G)$$


$I_C = 120.0 \text{ A}$



Typical capacitance as a function of collector-emitter voltage

$$C = f(V_{CE})$$


$f = 100 \text{ kHz}$, $V_{GE} = 0 \text{ V}$



4 Characteristics diagrams


Typical short circuit collector current as a function of gate-emitter voltage

$I_{C(SC)} = f(V_{GE})$
 $T_{vj} \leq 175\text{ }^{\circ}\text{C}, V_{CC} \leq 470\text{ V}$




Typical Short circuit withstand time as a function of gate-emitter voltage

$t_{SC} = f(V_{GE})$
 $T_{vj} \leq 175\text{ }^{\circ}\text{C}, V_{CC} \leq 470\text{ V}$




IGBT typical transient thermal impedance as a function of pulse width

$Z_{th(j-c)} = f(t_p)$
 $D = t_p/T$



Diode typical transient thermal impedance as a function of pulse width


$Z_{th(j-c)} = f(t_p)$
 $D = t_p/T$



4 Characteristics diagrams


Typical diode forward current as a function of forward voltage

$$I_F = f(V_F)$$



Typical diode forward voltage as a function of junction temperature


$$V_F = f(T_{vj})$$



Typical reverse recovery time as a function of diode current slope

$$t_{rr} = f(di_F/dt)$$


$$V_R = 470\text{ V}, I_F = 120.0\text{ A}$$



Typical reverse recovery charge as a function of diode current slope

$$Q_{rr} = f(di_F/dt)$$


$$V_R = 470\text{ V}, I_F = 120.0\text{ A}$$



4 Characteristics diagrams


Typical reverse recovery current as a function of diode current slope

$I_{rrm} = f(di_F/dt)$
 $V_R = 470\text{ V}, I_F = 120.0\text{ A}$



Typical diode peak rate of fall of reverse recovery current as a function of diode current slope

$di_{rr}/dt = f(di_F/dt)$
 $V_R = 470\text{ V}, I_F = 120.0\text{ A}$



5 Package outlines




Figure 1

Revision history

Document revision	Date of release	Description of changes
1.00	2022-02-16	Final datasheet
1.10	2022-04-07	Updated VF and Rthjc
1.20	2025-06-11	Package drawing, transient thermal impedance plots, and qualification labels updated according to the latest guidelines
1.30	2025-07-03	Qualification labels updated according to the latest guidelines

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2025-07-03

Published by

Infineon Technologies AG
81726 Munich, Germany

© 2025 Infineon Technologies AG
All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference
IFX-ABB226-004

Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.