

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: FZ1500R45KL3B5NPSA1
Manufacturer: Infineon Technologies
Package: Module
Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/infineon-technologies/fz1500r45kl3b5npsa1.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

Highly insulated module with Trench/Fieldstop IGBT3 and emitter controlled 3 diode

Features

- Electrical features
 - $V_{CES} = 4500\text{ V}$
 - $I_{C\text{ nom}} = 1500\text{ A} / I_{CRM} = 3000\text{ A}$
 - High DC stability
 - High dynamic robustness
 - Low $V_{CE,sat}$
 - Trench IGBT 3
 - $V_{CE,sat}$ with positive temperature coefficient
 - High short-circuit capability
- Mechanical features
 - High creepage and clearance distances
 - ALSiC base plate for increased thermal cycling capability
 - Package with enhanced insulation of 10.4 kV AC 60 s
 - Package with CTI > 600
 - Isolated base plate



Potential applications

- High-power converters
- Medium-voltage converters
- Motor drives
- Multi-level inverter
- Traction drives

Product validation

- Qualified for industrial applications according to the relevant tests of IEC 60747, 60749 and 60068

Description




Table of contents

	Description	1
	Features	1
	Potential applications	1
	Product validation	1
	Table of contents	2
1	Package	3
2	IGBT, Inverter	3
3	Diode, Inverter	5
4	Characteristics diagrams	7
5	Circuit diagram	11
6	Package outlines	12
7	Module label code	13
	Revision history	14
	Disclaimer	15

1 Package

Table 1 Insulation coordination

Parameter	Symbol	Note or test condition	Values	Unit
Isolation test voltage	V_{ISOL}	RMS, $f = 50 \text{ Hz}$, $t = 60 \text{ s}$	10.4	kV
Partial discharge extinction voltage	V_{isol}	RMS, $f = 50 \text{ Hz}$, $Q_{PD} \leq 10 \text{ pC}$	3.5	kV
DC stability	$V_{CE(D)}$	$T_{vj}=25^{\circ}\text{C}$, 100 Fit	3000	V
Material of module baseplate			AlSiC	
Internal isolation		basic insulation (class 1, IEC 61140)	AlN	
Creepage distance	d_{Creep}	terminal to heatsink	64.0	mm
Creepage distance	d_{Creep}	terminal to terminal	56.0	mm
Clearance	d_{Clear}	terminal to heatsink	40.0	mm
Clearance	d_{Clear}	terminal to terminal	26.0	mm
Comparative tracking index	CTI		> 600	

Table 2 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Stray inductance module	L_{sCE}			18		nH
Module lead resistance, terminals - chip	$R_{CC'+EE'}$	$T_C=25^{\circ}\text{C}$, per switch		0.12		mΩ
Storage temperature	T_{stg}		-55		125	°C
Mounting torque for module mounting	M	- Mounting according to valid application note	M6, Screw	4.25	5.75	Nm
Terminal connection torque	M	- Mounting according to valid application note	M4, Screw	1.8	2.1	Nm
			M8, Screw	8	10	
Weight	G			1400		g

Note: The maximum allowed dv/dt measured between 0,6 and $1 \times V_{ce}$ is 1400V/μs.

2 IGBT, Inverter

Table 3 Maximum rated values

Parameter	Symbol	Note or test condition	Values	Unit
Collector-emitter voltage	V_{CES}	$T_{vj} = -40^{\circ}\text{C}$	4500	V
		$T_{vj} = 25^{\circ}\text{C}$	4500	
		$T_{vj} = 125^{\circ}\text{C}$	4500	

(table continues...)

Table 3 (continued) Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Continuous DC collector current	I_{CDC}	$T_{vj\ max} = 150\ ^\circ\text{C}$	$T_C = 80\ ^\circ\text{C}$	1500	A
Repetitive peak collector current	I_{CRM}	t_p limited by $T_{vj\ op}$		3000	A
Gate-emitter peak voltage	V_{GES}			± 20	V

Table 4 Characteristic values

Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Collector-emitter saturation voltage	$V_{CE\ sat}$	$I_C = 1500\ \text{A}, V_{GE} = 15\ \text{V}$	$T_{vj} = 25\ ^\circ\text{C}$		2.70	3.05	V
			$T_{vj} = 125\ ^\circ\text{C}$		3.25	3.85	
Gate threshold voltage	V_{GETh}	$I_C = 105\ \text{mA}, V_{CE} = V_{GE}, T_{vj} = 25\ ^\circ\text{C}$		5.40	6	6.60	V
Gate charge	Q_G	$V_{GE} = \pm 15\ \text{V}, V_{CC} = 2800\ \text{V}$			39.5		μC
Internal gate resistor	R_{Gint}	$T_{vj} = 25\ ^\circ\text{C}$			0.75		Ω
Input capacitance	C_{ies}	$f = 1000\ \text{kHz}, T_{vj} = 25\ ^\circ\text{C}, V_{CE} = 25\ \text{V}, V_{GE} = 0\ \text{V}$			280		nF
Reverse transfer capacitance	C_{res}	$f = 1000\ \text{kHz}, T_{vj} = 25\ ^\circ\text{C}, V_{CE} = 25\ \text{V}, V_{GE} = 0\ \text{V}$			4.7		nF
Collector-emitter cut-off current	I_{CES}	$V_{CE} = 4500\ \text{V}, V_{GE} = 0\ \text{V}$	$T_{vj} = 25\ ^\circ\text{C}$			5	mA
Gate-emitter leakage current	I_{GES}	$V_{CE} = 0\ \text{V}, V_{GE} = 20\ \text{V}, T_{vj} = 25\ ^\circ\text{C}$				400	nA
Turn-on delay time (inductive load)	t_{don}	$I_C = 1500\ \text{A}, V_{CC} = 2800\ \text{V}, V_{GE} = \pm 15\ \text{V}, R_{Gon} = 0.68\ \Omega$	$T_{vj} = 25\ ^\circ\text{C}$		0.910		μs
			$T_{vj} = 125\ ^\circ\text{C}$		0.960		
Rise time (inductive load)	t_r	$I_C = 1500\ \text{A}, V_{CC} = 2800\ \text{V}, V_{GE} = \pm 15\ \text{V}, R_{Gon} = 0.68\ \Omega$	$T_{vj} = 25\ ^\circ\text{C}$		0.210		μs
			$T_{vj} = 125\ ^\circ\text{C}$		0.230		
Turn-off delay time (inductive load)	t_{doff}	$I_C = 1500\ \text{A}, V_{CC} = 2800\ \text{V}, V_{GE} = \pm 15\ \text{V}, R_{Goff} = 6.2\ \Omega$	$T_{vj} = 25\ ^\circ\text{C}$		7.310		μs
			$T_{vj} = 125\ ^\circ\text{C}$		7.710		
Fall time (inductive load)	t_f	$I_C = 1500\ \text{A}, V_{CC} = 2800\ \text{V}, V_{GE} = \pm 15\ \text{V}, R_{Goff} = 6.2\ \Omega$	$T_{vj} = 25\ ^\circ\text{C}$		1.020		μs
			$T_{vj} = 125\ ^\circ\text{C}$		1.970		
Turn-on time (resistive load)	t_{on_R}	$I_C = 500\ \text{A}, V_{CC} = 2000\ \text{V}, V_{GE} = \pm 15\ \text{V}, R_{Gon} = 0.68\ \Omega$	$T_{vj} = 25\ ^\circ\text{C}$	1.73			μs
Turn-on energy loss per pulse	E_{on}	$I_C = 1500\ \text{A}, V_{CC} = 2800\ \text{V}, L_\sigma = 110\ \text{nH}, V_{GE} = \pm 15\ \text{V}, R_{Gon} = 0.68\ \Omega, di/dt = 5200\ \text{A}/\mu\text{s} (T_{vj} = 125\ ^\circ\text{C})$	$T_{vj} = 25\ ^\circ\text{C}$		5200		mJ
			$T_{vj} = 125\ ^\circ\text{C}$		7500		

(table continues...)

Table 4 (continued) Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Turn-off energy loss per pulse	E_{off}	$I_C = 1500\text{ A}$, $V_{CC} = 2800\text{ V}$, $L_\sigma = 110\text{ nH}$, $V_{GE} = \pm 15\text{ V}$, $R_{Goff} = 6.2\ \Omega$, $dv/dt = 1300\text{ V}/\mu\text{s}$ ($T_{vj} = 125\text{ }^\circ\text{C}$)	$T_{vj} = 25\text{ }^\circ\text{C}$	6050		mJ
			$T_{vj} = 125\text{ }^\circ\text{C}$	7750		
SC data	I_{SC}	$V_{GE} \leq 15\text{ V}$, $V_{CC} = 2800\text{ V}$, $V_{CEmax} = V_{CES} - L_{sCE} \cdot di/dt$	$t_P = 10\ \mu\text{s}$, $T_{vj} = 125\text{ }^\circ\text{C}$	6900		A
Thermal resistance, junction to case	R_{thJC}	per IGBT			7.40	K/kW
Thermal resistance, case to heat sink	R_{thCH}	per IGBT, $\lambda_{grease} = 1\text{ W}/(\text{m}\cdot\text{K})$		9.00		K/kW
Temperature under switching conditions	$T_{vj\text{ op}}$		-50		125	$^\circ\text{C}$

3 Diode, Inverter

Table 5 Maximum rated values

Parameter	Symbol	Note or test condition		Values	Unit
Repetitive peak reverse voltage	V_{RRM}		$T_{\text{vj}} = -40\text{ }^{\circ}\text{C}$	4500	V
			$T_{\text{vj}} = 25\text{ }^{\circ}\text{C}$	4500	
			$T_{\text{vj}} = 125\text{ }^{\circ}\text{C}$	4500	
Continuous DC forward current	I_{F}			1500	A
Repetitive peak forward current	I_{FRM}	$t_{\text{P}} = 1\text{ ms}$		3000	A
I^2t - value	I^2t	$t_{\text{P}} = 10\text{ ms}$, $V_{\text{R}} = 0\text{ V}$	$T_{\text{vj}} = 125\text{ }^{\circ}\text{C}$	570	kA^2s
Maximum power dissipation	P_{RQM}		$T_{\text{vj}} = 125\text{ }^{\circ}\text{C}$	2400	kW
Minimum turn-on time	t_{onmin}			10	μs

Table 6 Characteristic values

Parameter	Symbol	Note or test condition	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	V_F	$I_F = 1500\text{ A}$, $V_{GE} = 0\text{ V}$	$T_{vj} = 25\text{ }^\circ\text{C}$	2.80	3.40	V
			$T_{vj} = 125\text{ }^\circ\text{C}$	2.70	3.20	
Peak reverse recovery current	I_{RM}	$V_{CC} = 2800\text{ V}$, $I_F = 1500\text{ A}$, $V_{GE} = -15\text{ V}$, $-di_F/dt = 5200\text{ A}/\mu\text{s}$ ($T_{vj} = 125\text{ }^\circ\text{C}$)	$T_{vj} = 25\text{ }^\circ\text{C}$	1600		A
			$T_{vj} = 125\text{ }^\circ\text{C}$	1800		

(table continues...)

Table 6 (continued) Characteristic values


Parameter	Symbol	Note or test condition		Values			Unit
				Min.	Typ.	Max.	
Recovered charge	Q_r	$V_{CC} = 2800 \text{ V}$, $I_F = 1500 \text{ A}$, $V_{GE} = -15 \text{ V}$, $-di_F/dt =$ $5200 \text{ A}/\mu\text{s}$ ($T_{vj} = 125 \text{ }^\circ\text{C}$)	$T_{vj} = 25 \text{ }^\circ\text{C}$		1300		μC
			$T_{vj} = 125 \text{ }^\circ\text{C}$		2500		
Reverse recovery energy	E_{rec}	$V_{CC} = 2800 \text{ V}$, $I_F = 1500 \text{ A}$, $V_{GE} = -15 \text{ V}$, $-di_F/dt =$ $5200 \text{ A}/\mu\text{s}$ ($T_{vj} = 125 \text{ }^\circ\text{C}$)	$T_{vj} = 25 \text{ }^\circ\text{C}$		2000		mJ
			$T_{vj} = 125 \text{ }^\circ\text{C}$		4300		
Thermal resistance, junction to case	R_{thJC}	per diode				17.0	K/kW
Thermal resistance, case to heat sink	R_{thCH}	per diode, $\lambda_{grease} = 1 \text{ W}/(\text{m}\cdot\text{K})$			14.0		K/kW
Temperature under switching conditions	$T_{vj\text{ op}}$			-50		125	$^\circ\text{C}$

4 Characteristics diagrams

Output characteristic (typical), IGBT, Inverter

$I_C = f(V_{CE})$


$V_{GE} = 15\text{ V}$



Output characteristic field (typical), IGBT, Inverter

$I_C = f(V_{CE})$


$T_{vj} = 125^\circ\text{C}$



Transfer characteristic (typical), IGBT, Inverter

$I_C = f(V_{GE})$


$V_{CE} = 20\text{ V}$



Switching losses (typical), IGBT, Inverter

$E = f(I_C)$


$R_{Goff} = 6.2\ \Omega$, $R_{Gon} = 0.68\ \Omega$, $V_{CC} = 2800\text{ V}$, $V_{GE} = -15 / 15\text{ V}$



4 Characteristics diagrams


Switching losses (typical), IGBT, Inverter

$E = f(R_G)$
 $I_C = 1500\text{ A}$, $V_{CC} = 2800\text{ V}$, $V_{GE} = -15 / 15\text{ V}$




Switching times (typical), IGBT, Inverter

$t = f(I_C)$
 $R_{Goff} = 6.2\text{ }\Omega$, $R_{Gon} = 0.68\text{ }\Omega$, $V_{GE} = \pm 15\text{ V}$, $V_{CC} = 2800\text{ V}$, $T_{vj} = 125\text{ }^\circ\text{C}$




Switching times (typical), IGBT, Inverter

$t = f(R_G)$
 $V_{GE} = \pm 15\text{ V}$, $I_C = 1500\text{ A}$, $V_{CC} = 2800\text{ V}$, $T_{vj} = 125\text{ }^\circ\text{C}$



Transient thermal impedance , IGBT, Inverter


$Z_{th} = f(t)$



Reverse bias safe operating area (RBSOA), IGBT, Inverter

$$I_C = f(V_{CE})$$


$$R_{Goff} = 6.2 \, \Omega, V_{GE} = \pm 15 \, V, T_{vj} = 125 \, ^\circ C$$



Capacity characteristic (typical), IGBT, Inverter

$$C = f(V_{CE})$$


$$f = 1000 \, kHz, V_{GE} = 0 \, V, T_{vj} = 25 \, ^\circ C$$



Gate charge characteristic (typical), IGBT, Inverter


$$V_{GE} = f(Q_G)$$

$$I_C = 1500 \, A, T_{vj} = 25 \, ^\circ C$$



Forward characteristic (typical), Diode, Inverter


$$I_F = f(V_F)$$



4 Characteristics diagrams


Switching losses (typical), Diode, Inverter

$E_{rec} = f(I_F)$
 $R_{Gon} = R_{Gon}(IGBT) , V_{CC} = 2800\text{ V}$




Switching losses (typical), Diode, Inverter

$E_{rec} = f(R_G)$
 $I_F = 1500\text{ A}, V_{CC} = 2800\text{ V}$




Transient thermal impedance, Diode, Inverter

$Z_{th} = f(t)$



Safe operating area (SOA), Diode, Inverter

$I_R = f(V_R)$
 $T_{vj} = 125\text{ }^\circ\text{C}$



5 Circuit diagram




Figure 1




Figure 2

7 Module label code

Module label code			
Code format	Data Matrix		Barcode Code128
Encoding	ASCII text		Code Set A
Symbol size	16x16		23 digits
Standard	IEC24720 and IEC16022		IEC8859-1
Code content	Content	Digit	Example
	Module serial number	1 – 5	71549
	Module material number	6 - 11	142846
	Production order number	12 - 19	55054991
	Date code (production year)	20 – 21	15
	Date code (production week)	22 – 23	30
Example	 71549142846550549911530  71549142846550549911530		

Figure 3

Revision history

Document revision	Date of release	Description of changes
0.10	2021-09-15	Initial version
0.20	2022-02-24	Target datasheet
0.30	2022-05-16	Preliminary datasheet
1.00	2022-08-15	Final datasheet

Trademarks

All referenced product or service names and trademarks are the property of their respective owners.

Edition 2022-08-15

Published by

Infineon Technologies AG

81726 Munich, Germany

© 2022 Infineon Technologies AG

All Rights Reserved.

Do you have a question about any aspect of this document?

Email: erratum@infineon.com

Document reference

IFX-ABC166-004

Important notice

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics ("Beschaffenhheitsgarantie").

With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of Infineon Technologies in customer's applications.

The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

Please note that this product is not qualified according to the AEC Q100 or AEC Q101 documents of the Automotive Electronics Council.

Warnings

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest Infineon Technologies office.

Except as otherwise explicitly approved by Infineon Technologies in a written document signed by authorized representatives of Infineon Technologies, Infineon Technologies' products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.