

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: 0311010.H
Manufacturer: Littelfuse Inc.
Package: Bulk
Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/littelfuse-inc/0311010-h.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

LOW VOLTAGE

SFE Fast-Acting Type

ELECTRICAL CHARACTERISTICS:

% of Ampere Rating	Opening Time
110%	4 hours, Minimum
135%	1 hour, Maximum
200%	10 seconds, Maximum

APPROVALS: Listed by Underwriters Laboratories.

DESIGN STANDARDS: U.L. Standard 275. SAE (Society of Automotive Engineers) J554.



FUSE DIMENSIONS:
Diameter: 1/4"
Length: See chart.



ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating	Fuse Length
307 004	4	32	5/8"
307 006	6	32	3/4"
307 07.5	7 1/2	32	7/8"
307 009	9	32	7/8"
307 014	14	32	1 1/16"
307 020	20	32	1 1/4"
307 030	30	32	1 7/16"

3AG Fast-Acting Type

ELECTRICAL CHARACTERISTICS:


% of Ampere Rating	Ampere Rating	Opening Time
100%	4-35	4 hours, Minimum
135%	4-35	1 hour, Maximum
200%	4-30	10 seconds, Maximum
200%	35	20 seconds, Maximum

APPROVALS: Listed by Underwriters Laboratories and Certified by CSA through 30 amperes.

DESIGN STANDARDS: U.L. Standard 275.



FUSE DIMENSIONS:
Diameter: 1/4"
Length: 1 1/4"



ORDERING INFORMATION:

Catalog Number	Ampere Rating	Voltage Rating
311 004	4	32
311 005	5	32
311 006	6	32
311 007	7	32
311 07.5	7 1/2	32
311 008	8	32
311 010	10	32
311 012	12	32
311 015	15	32
311 025	25	32
311 030	30	32
311 035	35	32

For 20-ampere rating use 307 020.