

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: MICROSM075-2
Manufacturer: Littelfuse Inc.
Package: 1210 (3225 Metric), Concave
Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/littelfuse-inc/microsmd075-2.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

Raychem Corporation
300 Constitution Drive
Menlo Park, CA 94025
800-227-4856
FAX 800-227-4866

Raychem
PolySwitch®
PTC Devices
Overcurrent Protection Device

PRODUCT: microSMD075

DOCUMENT: SCD 24403
PCN: 448359
REV LETTER: D
REV DATE: FEBRUARY 26, 2000
PAGE NO.: 1 OF 1

Specification Status: Released

Maximum Electrical Rating

Voltage: 6V_{DC}
Current: 40A

Notes:

1. All terminations are tin/lead plated.
2. Devices can be wave soldered.
3. Drawing not to scale

Marking:





TABLE I. DIMENSIONS:

	A		B		C		D	E
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MIN
mm:	3.00	3.43	2.35	2.80	0.38	0.62	0.25	0.20
in:*	0.118	0.135	0.092	0.111	0.015	0.025	0.010	0.008

*Rounded off approximation

TABLE II. PERFORMANCE RATINGS:

IHOLD ** RATED CURRENT	CURRENT TRIP LIMITS**						TIME TO TRIP **		RESISTANCE VALUES		TRIPPED- STATE POWER DISSIPATION**
	AMPERES AT 20°C HOLD	AMPERES AT -40°C HOLD	AMPERES AT 20°C TRIP	AMPERES AT 60°C HOLD	AMPERES AT 60°C TRIP	AMPERES AT 60°C TRIP	SECONDS AT 20°C, 5A MAX	SECONDS AT 20°C, 8A MAX	OHMS AT 20°C MIN	OHMS AT 20°C MAX*	
0.75	1.10	2.20	0.75	1.50	0.55	1.10	0.5	0.1	0.110	0.40	0.8

*Maximum resistance is measured 1 hour after reflow.

** Values specified were determined using PCB's with 0.030"X1.5 ounce copper traces.

Reference Documents:

PS300, E. N. SMD1.0x

Precedence:

This specification takes precedence over documents referenced herein.

Effectivity:

Reference documents shall be the issue in effect on the date of invitation for bid.

CAUTION:

Operation beyond the rated voltage or current may result in rupture, electrical arcing or flame.