

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: MPF102_D74Z
Manufacturer: onsemi
Package: Please confirm with sales
Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/onsemi/mpf102-d74z.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request


Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

MPF102



N-Channel RF Amplifier

This device is designed for electronic switching
Applications such as low ON resistance analog switching.
Sourced from Process 50.

Absolute Maximum Ratings * TA=25 degree C unless otherwise noted

Symbol	Parameter	Value	Units
V _{DG}	Drain-Gate Voltage	25	V
V _{GS}	Gate-Source Voltage	-25	V
I _{GF}	Forward Gate Current	10	mA
T _J , T _{stg}	Operating and Storage Junction Temperature Range	-55 to + 155	degree C

* This ratings are limiting values above which the serviceability of any semiconductor device may be impaired.

NOTES :

- 1) These rating are based on a maximum junction temperature of 150 degrees C.
- 2) These are steady state limits. The factory should be consulted on applications involving pulsed or low duty cycle operations.

Thermal Characteristics TA = 25 degrees C unless otherwise noted.

Symbol	Characteristic	Max	Units
P _D	Total Device Dissipation Derate above 25 degrees C	350 2.8	mW mW/degrees C
R _{θJC}	Thermal Resistance, Junction to Case	125	degrees C/W
R _{θJA}	Thermal Resistance, Junction to Ambient	357	degrees C/W

* Device mounted on FR-4 PCB 1.5" X 1.6" X 0.06"

N-Channel RF Amplifier

(Continued)

Electrical Characteristics

TA= 25 degrees C unless otherwise noted

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
OFF CHARACTERISTICS						
V _{(BR)GSS}	Gate-Source Breakdown Voltage	I _G =-1.0μA, V _{DS} =0	-25			V
I _{GSS}	Gate Reverse Current	V _{GS} =-15V, V _{DS} =0			-2.0	nA
V _{GS(off)}	Gate-Source Cutoff Voltage	V _{DS} =15V, I _D =2nA			-8.0	V
V _{GS}	Gate-Source Voltage	V _{DS} =15V, I _D =200μA	-0.5		-7.5	V
ON CHARACTERISTICS						
I _{DSS}	Zero-Gate Voltage Drain Current	V _{DS} =15V, V _{GS} =0	2.0		20	mA
g _{fs}	Forward Transconductance	V _{GS} = 0V, V _{DS} =15V, f=1kHz.	2000		7500	μS
Capacitance						
C _{iss}	Common-Source Input Capacitance	V _{GS} =15V, V _{DS} =0V f=1 MHz.			7.0	pf
C _{rss}	Common-Source reverse Transfer Capacitance	V _{GS} =15V, V _{DS} =0V f=1 MHz.			3.0	pf

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACE [™]	FAST [™]	PowerTrench [®]	SyncFET [™]
Bottomless [™]	GlobalOptoisolator [™]	QFET [™]	TinyLogic [™]
CoolFET [™]	GTO [™]	QS [™]	UHC [™]
CROSSVOLT [™]	HiSeC [™]	QT Optoelectronics [™]	VCX [™]
DOVE [™]	ISOPLANAR [™]	Quiet Series [™]	
E ² CMOS [™]	MICROWIRE [™]	SILENT SWITCHER [®]	
EnSigna [™]	OPTOLOGIC [™]	SMART START [™]	
FACT [™]	OPTOPLANAR [™]	SuperSOT [™] -3	
FACT Quiet Series [™]	PACMAN [™]	SuperSOT [™] -6	
FAST [®]	POP [™]	SuperSOT [™] -8	

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.