

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: DB2G60800L1

Manufacturer: Panasonic Electronic Components

Package: 0402 (1005 Metric)

Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/panasonic-electronic-components/db2g60800l1.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

Panasonic

DB2G60800L1

For rectification

■ Features

- Low forward voltage VF
- Forward current (Average) IF(AV) ≤ 1.0 A rectification is possible
- RoHS compliant
- (EU RoHS / MSL:Level 1 compliant)

■ Marking Symbol: D7

■ Packaging

Embossed type (Thermo-compression sealing) : 1 000 pcs / reel (standard)

■ Absolute Maximum Ratings

Parameter	Symbol	Min	Max	Unit
Reverse Voltage ^{*1}	VR	-	60	V
Maximum Peak Reverse Voltage ^{*1}	VRM	-	60	V
Average Forward Current ^{*2,3}	IF(AV)	-	1.0	A
Average Forward Current ^{*2,4}	IF(AV)	-	1.0	A
Non-repetitive Peak Surge Forward Current ^{*1,5}	IFSM	-	10	A
Operating Junction Temperature ^{*6}	Tj	-	150	°C
Ambient Temperature	Ta	-40	+150	°C
Storage Temperature	Tstg	-55	+150	°C

Note) ^{*1}: Ta = Tj = 25°C


^{*2}: Square wave : σ = 0.5

^{*3}: Ta ≤ 85°C, when device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), (620.0mm² area, 36μm thick).

^{*4}: Solder Point Temperature : Tsp ≤ 135°C


^{*5}: Square wave : Tp = 5 ms

^{*6}: Power derating is necessary so that Tj < 150°C.



(Waveform definition)

$$\text{Duty Cycle : } \sigma = \frac{T_p}{T}$$



■ Electrical Characteristics Ta = 25 °C ± 3 °C

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward Voltage	VF	IF = 1.0 A	-	0.6	0.68	V
Reverse Current	IR	VR = 60 V	-	3	40	μA
Terminal Capacitance	Ct	VR = 10 V, f = 1 MHz	-	20	-	pF
Reverse Recovery Time ^{*1}	trr	IF = IR = 100 mA, Irr = 10 mA	-	6.6	-	ns


Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7031 measuring methods for diodes.

2. This product is sensitive to electric shock (static electricity, etc.).


Due attention must be paid on the charge of a human body and the leakage of current from the operating equipment.

3. ^{*1}: Measurement circuit, input pulse, output pulse for Reverse recovery time


(Measurement circuit)



(Input pulse)




(Output pulse)






Electrical Characteristics Technical Data (Reference)


IF - VF / Typical Data



Ct - VR / Typical Data



IR - VR / Typical Data




(Graph legends)

(1)	Ta = 150 °C
(2)	Ta = 125 °C
(3)	Ta = 85 °C
(4)	Ta = 25 °C
(5)	Ta = -40 °C




Electrical Characteristics Technical Data (Reference)

PF(AV) - IF(AV) / Typical Data



(Waveform definition)




Duty Cycle : $\sigma = \frac{T_p}{T}$


(Graph legends)

(1)	$\sigma = 1.0$
(2)	$\sigma = 0.8$
(3)	$\sigma = 0.5$
(4)	$\sigma = 0.3$

PR(AV) - VR / Typical Data



(Waveform definition)



Duty Cycle : $\sigma = \frac{T_p}{T}$


(Graph legends)

(1)	$\sigma = 1.0$
(2)	$\sigma = 0.7$
(3)	$\sigma = 0.5$
(4)	$\sigma = 0.2$




Electrical Characteristics Technical Data (Reference)

PF(AV) - IF(AV) / Typical Data




PR(AV) - VR / Typical Data




Thermal Characteristics

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Thermal Resistance, Junction to Solder Point	$R_{th(j-sp)}$	$T_a = 25^{\circ}C$, in free air	-	20	-	$^{\circ}C/W$
Thermal Resistance, Junction to Ambient ^{*1}	$R_{th(j-a)}$	$T_a = 25^{\circ}C$, in free air	-	92	-	$^{\circ}C/W$
Thermal Resistance, Junction to Ambient ^{*2}	$R_{th(j-a)}$	$T_a = 25^{\circ}C$, in free air	-	170	-	$^{\circ}C/W$


Note) ^{*1}: Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (620.0mm² area, 36μm thick).
^{*2}: Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (108.6mm² area, 36μm thick).



Thermal Characteristics Technical Data (Reference)



Note) ^{*1}: Single pulse measurement
(Waveform definition)




(Graph legends)


(1)	Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (108.6mm ² area, 36μm thick).
(2)	Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (620.0mm ² area, 36μm thick).

Thermal Characteristics Technical Data (Reference)


Effective Transient Thermal Resistance - T_p^{*1} / Typical Data



(Evaluation board outline)



(Waveform definition)




$$\text{Duty Cycle : } \sigma = \frac{T_p}{T}$$

(Graph legends)

(1)	$\sigma = 0.5$
(2)	$\sigma = 0.2$
(3)	$\sigma = 0.1$
(4)	$\sigma = 0.05$
(5)	$\sigma = 0.02$
(6)	$\sigma = 0$


Effective Transient Thermal Resistance - T_p^{*2} / Typical Data



(Evaluation board outline)



(Waveform definition)



$$\text{Duty Cycle : } \sigma = \frac{T_p}{T}$$

(Graph legends)


(1)	$\sigma = 0.5$
(2)	$\sigma = 0.2$
(3)	$\sigma = 0.1$
(4)	$\sigma = 0.05$
(5)	$\sigma = 0.02$
(6)	$\sigma = 0$

Note) *1: Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (108.6mm² area, 36μm thick).


*2: Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (620.0mm² area, 36μm thick).

Power Derating Technical Data (Reference)


IF(AV) - Ta^{*1} / Typical Data



IF(AV) - Ta^{*2} / Typical Data




IF(AV) - Tsp / Typical Data



(Graph legends)

(1)	$\sigma = 1.0$
(2)	$\sigma = 0.8$
(3)	$\sigma = 0.5$
(4)	$\sigma = 0.3$

(Waveform definition)



Note)

*1: Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (108.6mm² area, 36μm thick).

(Evaluation board outline)



*2: Device mounted on a FR4 PCB (25.4mm×25.4mm, 1mm thick), copper wiring (620.0mm² area, 36μm thick).

(Evaluation board outline)






Schottky Barrier Diode
DB2G60800L1


DCSP1006010-N1

Unit: mm



■ Land Pattern (Reference)

Unit: mm



Request for your special attention and precautions in using the technical information and semiconductors described in this book

- (1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.
- (2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products. No license is granted in and to any intellectual property right or other right owned by Panasonic Corporation or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information de-scribed in this book.
- (3) The products described in this book are intended to be used for general applications (such as office equipment, communications equipment, measuring instruments and household appliances), or for specific applications as expressly stated in this book.
Please consult with our sales staff in advance for information on the following applications, moreover please exchange documents separately on terms of use etc.: Special applications (such as for in-vehicle equipment, airplanes, aerospace, automotive equipment, traffic signaling equipment, combustion equipment, medical equipment and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
Unless exchanging documents on terms of use etc. in advance, it is to be understood that our company shall not be held responsible for any damage incurred as a result of or in connection with your using the products described in this book for any special application.
- (4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.
- (5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.
- (6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. We do not guarantee quality for disassembled products or the product re-mounted after removing from the mounting board.
When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.
- (7) When reselling products described in this book to other companies without our permission and receiving any claim of request from the resale destination, please understand that customers will bear the burden.
- (8) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of our company.