

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: RSS110N03FU6TB
Manufacturer: Rohm Semiconductor
Package: Please confirm with sales
Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/rohm-semiconductor/rss110n03fu6tb.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

Switching (30V, ± 11 A)

RSS110N03


●Features

- 1) Low on-resistance.
- 2) Built-in G-S Protection Diode.
- 3) Small and Surface Mount Package (SOP8).

●Applications

Power switching, DC/DC converter.


●External dimensions (Unit : mm)



●Structure

- Silicon N-channel MOS FET

●Equivalent circuit



*A protection diode is included between the gate and the source terminals to protect the diode against static electricity when the product is in use. Use the protection circuit when the fixed voltages are exceeded.

●Absolute maximum ratings (Ta=25°C)

Parameter	Symbol	Limits	Unit
Drain-source voltage	V_{DS}	30	V
Gate-source voltage	V_{GS}	20	V
Drain current	Continuous	I_D	± 11 A
	Pulsed	I_{DP}	± 44 A *1
Source current (Body diode)	Continuous	I_S	1.6 A
	Pulsed	I_{SP}	6.4 A *1
Total power dissipatino	P_D	2	W *2
Channel temperature	T_{ch}	150	°C
Strage temperature	T_{stg}	-55 to +150	°C

*1 $P_w \leq 10 \mu s$, Duty cycle $\leq 1\%$

*2 Mounted on a ceramic board.

Transistor

●Thermal resistance (Ta=25°C)

Parameter	Symbol	Limits	Unit
Channel to ambient	Rth (ch-a)	62.5	°C / W *

* Mounted on a ceramic board.

●Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Gate-source leakage	I _{GSS}	—	—	10	μA	V _{GS} =20V, V _{DS} =0V
Drain-source breakdown voltage	V _{(BR) DSS}	30	—	—	V	I _D =1mA, V _{GS} =0V
Zero gate voltage drain current	I _{DSS}	—	—	10	μA	V _{DS} =30V, V _{GS} =0V
Gate threshold voltage	V _{GS(th)}	1.0	—	2.5	V	V _{DS} =10V, I _D =1mA
Static drain-source on-state resistance	R _{DS(on)}	—	7.6	10.4	mΩ	I _D =±11A, V _{GS} =10V *
		—	10.3	14.3		I _D =±11A, V _{GS} =4.5V *
		—	11.2	15.5		I _D =±11A, V _{GS} =4V *
Forward transfer admittance	Y _{fs}	8.0	—	—	S	I _D =±11A, V _{DS} =10V *
Input capacitance	C _{iss}	—	1300	—	pF	V _{DS} =10V
Output capacitance	C _{oss}	—	410	—	pF	V _{GS} =0V
Reverse transfer capacitance	C _{rss}	—	250	—	pF	f=1MHz
Turn-on delay time	t _{d(on)}	—	9	—	ns	I _D =5.5A, V _{DD} ≐15V *
Rise time	t _r	—	17	—	ns	V _{GS} =10V *
Turn-off delay time	t _{d(off)}	—	60	—	ns	R _L =2.73Ω *
Fall time	t _f	—	30	—	ns	R _{GS} =10Ω *
Total gate charge	Q _g	—	17	—	nC	V _{DD} ≐15V *
Gate-source charge	Q _{gs}	—	3.3	—	nC	V _{GS} =5V *
Gate-drain charge	Q _{gd}	—	7.1	—	nC	I _D =±11A *

* Pulsed

●Body diode characteristics (Source-Drain Characteristics) (Ta=25°C)

Parameter	Symbol	Min.	Typ.	Max.	Unit	Conditions
Forward voltage	V _{SD}	—	—	1.2	V	I _S =6.4A, V _{GS} =0V *

* Pulsed

●Electrical characteristic curves




Fig.1 Typical Capacitance vs. Drain-Source Voltage




Fig.2 Switching Characteristics




Fig.3 Dynamic Input Characteristics

Transistor









Fig.4 Typical Transfer Characteristics

Fig.5 Static Drain-Source
On-State Resistance vs.
Gate-Source VoltageFig.6 Source Current vs.
Source-Drain VoltageFig.7 Static Drain-Source
On-State Resistance
vs. Drain Current (I)Fig.8 Static Drain-Source
On-State Resistance
vs. Drain Current (II)Fig.9 Static Drain-Source
On-State Resistance
vs. Drain Current (III)

Notes

- No technical content pages of this document may be reproduced in any form or transmitted by any means without prior permission of ROHM CO.,LTD.
- The contents described herein are subject to change without notice. The specifications for the product described in this document are for reference only. Upon actual use, therefore, please request that specifications to be separately delivered.
- Application circuit diagrams and circuit constants contained herein are shown as examples of standard use and operation. Please pay careful attention to the peripheral conditions when designing circuits and deciding upon circuit constants in the set.
- Any data, including, but not limited to application circuit diagrams information, described herein are intended only as illustrations of such devices and not as the specifications for such devices. ROHM CO.,LTD. disclaims any warranty that any use of such devices shall be free from infringement of any third party's intellectual property rights or other proprietary rights, and further, assumes no liability of whatsoever nature in the event of any such infringement, or arising from or connected with or related to the use of such devices.
- Upon the sale of any such devices, other than for buyer's right to use such devices itself, resell or otherwise dispose of the same, no express or implied right or license to practice or commercially exploit any intellectual property rights or other proprietary rights owned or controlled by
- ROHM CO., LTD. is granted to any such buyer.
- Products listed in this document use silicon as a basic material.
Products listed in this document are no antiradiation design.

The products listed in this document are designed to be used with ordinary electronic equipment or devices (such as audio visual equipment, office-automation equipment, communications devices, electrical appliances and electronic toys).

Should you intend to use these products with equipment or devices which require an extremely high level of reliability and the malfunction of which would directly endanger human life (such as medical instruments, transportation equipment, aerospace machinery, nuclear-reactor controllers, fuel controllers and other safety devices), please be sure to consult with our sales representative in advance.

About Export Control Order in Japan

Products described herein are the objects of controlled goods in Annex 1 (Item 16) of Export Trade Control Order in Japan.

In case of export from Japan, please confirm if it applies to "objective" criteria or an "informed" (by MITI clause) on the basis of "catch all controls for Non-Proliferation of Weapons of Mass Destruction.