

ANTREX Electronics

Electronic Components Sourcing Information

Product Reference Information

Part Number: 2SB1647
Manufacturer: Sanken Electric USA Inc.
Package: TO-3P-3, SC-65-3
Availability: Please confirm with sales

Product Page:

<https://antrexco.com/product/details/sanken-electric-usa-inc/2sb1647.html>

Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

Contact Information

Email: info@antrexco.com

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects


Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

Darlington

2SB1647



Silicon PNP Epitaxial Planar Transistor (Complement to type 2SD2560)

Application : Audio, Series Regulator and General Purpose

■ **Absolute maximum ratings** ($T_a=25^\circ\text{C}$)

Symbol	Ratings	Unit
V_{CB0}	-150	V
V_{CE0}	-150	V
V_{EB0}	-5	V
I_C	-15	A
I_B	-1	A
P_c	130($T_c=25^\circ\text{C}$)	W
T_j	150	$^\circ\text{C}$
T_{stg}	-55 to +150	$^\circ\text{C}$

■ **Electrical Characteristics** ($T_a=25^\circ\text{C}$)


Symbol	Conditions	Ratings	Unit
I_{CBO}	$V_{CB}=-150\text{V}$	-100max	μA
I_{EBO}	$V_{EB}=-5\text{V}$	-100max	μA
$V_{(BR)CEO}$	$I_C=-30\text{mA}$	-150min	V
h_{FE}	$V_{CE}=-4\text{V}$, $I_C=-10\text{A}$	5000min*	
$V_{CE(sat)}$	$I_C=-10\text{A}$, $I_B=-10\text{mA}$	-2.5max	V
$V_{BE(sat)}$	$I_C=-10\text{A}$, $I_B=-10\text{mA}$	-3.0max	V
f_T	$V_{CE}=-12\text{V}$, $I_E=2\text{A}$	45typ	MHz
C_{OB}	$V_{CB}=-10\text{V}$, $f=1\text{MHz}$	320typ	pF

* h_{FE} Rank O(5000 to 12000), P(6500 to 20000), Y(15000 to 30000)


■ **Typical Switching Characteristics (Common Emitter)**

V_{CC} (V)	R_L (Ω)	I_C (A)	V_{BB1} (V)	V_{BB2} (V)	I_{B1} (mA)	I_{B2} (mA)	t_{on} (μs)	t_{stg} (μs)	t_f (μs)
-40	4	10	-10	5	-10	10	0.7typ	1.6typ	1.1typ


External Dimensions MT-100(TO3P)




I_C-V_{CE} Characteristics (Typical)




$V_{CE(sat)}-I_B$ Characteristics (Typical)




I_C-V_{BE} Temperature Characteristics (Typical)




$h_{FE}-I_C$ Characteristics (Typical)




$h_{FE}-I_C$ Temperature Characteristics (Typical)




$\theta_{JA}-t$ Characteristics



f_T-I_E Characteristics (Typical)



Safe Operating Area (Single Pulse)



P_c-T_a Derating

