

# ANTREX Electronics

## Electronic Components Sourcing Information

---

### Product Reference Information

|                      |                                                |
|----------------------|------------------------------------------------|
| <b>Part Number:</b>  | GBU4G-M3/51                                    |
| <b>Manufacturer:</b> | Vishay General Semiconductor - Diodes Division |
| <b>Package:</b>      | 4-SIP, GBU                                     |
| <b>Availability:</b> | Please confirm with sales                      |

#### Product Page:

<https://antrexco.com/product/details/vishay-general-semiconductor-diodes-division/gbu4g-m3-51.html>



Scan for product page

#### Request a Quote:

[Submit RFQ for this part](#)

### Contact Information

Email: [info@antrexco.com](mailto:info@antrexco.com)

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

### Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

#### Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.


---



## Glass Passivated Single-Phase Bridge Rectifier



Case Style GBU



Case Style GBU



**RoHS**  
COMPLIANT  
HALOGEN  
**FREE**

### FEATURES

- UL recognition file number E54214
- Ideal for printed circuit boards
- High surge current capability
- High case dielectric strength of 1500 V<sub>RMS</sub>
- Solder dip 275 °C max. 10 s, per JESD 22-B106
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)

### TYPICAL APPLICATIONS

General purpose use in AC/DC bridge full wave rectification for monitor, TV, printer, switching mode power supply, adapter, audio equipment, and home appliances applications.

### LINKS TO ADDITIONAL RESOURCES



| PRIMARY CHARACTERISTICS |                                                 |
|-------------------------|-------------------------------------------------|
| $I_{F(AV)}$             | 4.0 A                                           |
| $V_{RRM}$               | 50 V, 100 V, 200 V, 400 V, 600 V, 800 V, 1000 V |
| $I_{FSM}$               | 150 A                                           |
| $I_R$                   | 5 $\mu$ A                                       |
| $V_F$ at $I_F = 4.0$ A  | 1.0 V                                           |
| $T_J$ max.              | 150 °C                                          |
| Package                 | GBU                                             |
| Circuit configuration   | In-line                                         |

### MECHANICAL DATA

**Case:** GBU

Molding compound meets UL 94 V-0 flammability rating  
Base P/N-E3 - RoHS-compliant, commercial grade  
Base P/N-M3 - halogen-free, RoHS-compliant, and commercial grade

**Terminals:** matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 and M3 suffix meet JESD 201 class 1A whisker test

**Polarity:** as marked on body

**Mounting Torque:** 10 cm·kg (8.8 inches·lbs) max.

**Recommended Torque:** 5.7 cm·kg (5 inches·lbs)

| MAXIMUM RATINGS (T <sub>A</sub> = 25 °C unless otherwise noted)                                                                        |                                   |             |       |       |       |       |       |       |                  |
|----------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|-------------|-------|-------|-------|-------|-------|-------|------------------|
| PARAMETER                                                                                                                              | SYMBOL                            | GBU4A       | GBU4B | GBU4D | GBU4G | GBU4J | GBU4K | GBU4M | UNIT             |
| Maximum repetitive peak reverse voltage                                                                                                | V <sub>RRM</sub>                  | 50          | 100   | 200   | 400   | 600   | 800   | 1000  | V                |
| Maximum RMS voltage                                                                                                                    | V <sub>RMS</sub>                  | 35          | 70    | 140   | 280   | 420   | 560   | 700   | V                |
| Maximum DC blocking voltage                                                                                                            | V <sub>DC</sub>                   | 50          | 100   | 200   | 400   | 600   | 800   | 1000  | V                |
| Maximum average forward rectified output current at<br>T <sub>C</sub> = 100 °C <sup>(1)</sup><br>T <sub>A</sub> = 40 °C <sup>(2)</sup> | I <sub>F(AV)</sub>                | 4.0         |       |       |       |       |       |       | A                |
|                                                                                                                                        |                                   | 3.0         |       |       |       |       |       |       |                  |
| Peak forward surge current single sine-wave superimposed on rated load                                                                 | I <sub>FSM</sub>                  | 150         |       |       |       |       |       |       | A                |
| Rating for fusing (t < 8.3 ms)                                                                                                         | I <sup>2</sup> t                  | 93          |       |       |       |       |       |       | A <sup>2</sup> s |
| Operating junction and storage temperature range                                                                                       | T <sub>J</sub> , T <sub>STG</sub> | -55 to +150 |       |       |       |       |       |       | °C               |

### Notes

<sup>(1)</sup> Unit case mounted on 1.6" x 1.6" x 0.06" thick (4.0 cm x 4.0 cm x 0.15 cm) aluminum plate

<sup>(2)</sup> Units mounted on PCB with 0.5" x 0.5" (12 mm x 12 mm) copper pads and 0.375" (9.5 mm) lead length

**ELECTRICAL CHARACTERISTICS** ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

| PARAMETER                                                         | TEST CONDITIONS         | SYMBOL         | GBU4A | GBU4B | GBU4D | GBU4G | GBU4J | GBU4K | GBU4M | UNIT |
|-------------------------------------------------------------------|-------------------------|----------------|-------|-------|-------|-------|-------|-------|-------|------|
| Maximum instantaneous forward voltage drop per diode              | 4.0 A                   | V <sub>F</sub> | 1.0   |       |       |       |       |       |       | V    |
| Maximum DC reverse current at rated DC blocking voltage per diode | T <sub>A</sub> = 25 °C  | I <sub>R</sub> | 5.0   |       |       |       |       |       |       | μA   |
|                                                                   | T <sub>A</sub> = 125 °C |                | 500   |       |       |       |       |       |       |      |
| Typical junction capacitance per diode                            | 4 V, 1 MHz              | C <sub>J</sub> | 57    |       |       |       |       |       |       | pF   |

**THERMAL CHARACTERISTICS** ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

| PARAMETER                  | SYMBOL                          | GBU4A | GBU4B | GBU4D | GBU4G | GBU4J | GBU4K | GBU4M | UNIT |
|----------------------------|---------------------------------|-------|-------|-------|-------|-------|-------|-------|------|
| Typical thermal resistance | R <sub>θJA</sub> <sup>(2)</sup> | 22    |       |       |       |       |       |       | °C/W |
|                            | R <sub>θJC</sub> <sup>(1)</sup> | 4.2   |       |       |       |       |       |       |      |

**Notes**

- (1) Units case mounted on aluminum plate heatsink  
(2) Units mounted in free air, no heatsink on PCB, 0.5" x 0.5" (12 mm x 12 mm) copper pads, 0.375" (9.5 mm) lead length

**ORDERING INFORMATION**

| PREFERRED P/N | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE |
|---------------|-----------------|------------------------|---------------|---------------|
| GBU4J-E3/45   | 3.857           | 45                     | 20            | Tube          |
| GBU4J-E3/51   | 3.857           | 51                     | 250           | Paper tray    |
| GBU4J-M3/45   | 3.565           | 45                     | 20            | Tube          |
| GBU4J-M3/51   | 3.565           | 51                     | 250           | Paper tray    |


**RATINGS AND CHARACTERISTICS CURVES** ( $T_A = 25\text{ }^{\circ}\text{C}$  unless otherwise noted)

Fig. 1 - Derating Curve Output Rectified Current




Fig. 2 - Maximum Non-Repetitive Peak Forward Surge Current Per Diode




Fig. 3 - Typical Forward Characteristics Per Diode




Fig. 5 - Typical Junction Capacitance Per Diode




Fig. 4 - Typical Reverse Leakage Characteristics Per Diode





Fig. 6 - Typical Transient Thermal Impedance

## PACKAGE OUTLINE DIMENSIONS in inches (millimeters)

### Case Type GBU



Polarity shown on front side of case, positive lead by beveled corner



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.