

# ANTREX Electronics

Electronic Components Sourcing Information

---

## Product Reference Information

**Part Number:** VS-150UR120DM12

**Manufacturer:** Vishay General Semiconductor - Diodes Division

**Package:** DO-205AA, DO-8, Stud


**Availability:** Please confirm with sales

### Product Page:

<https://antrexco.com/product/details/vishay-general-semiconductor-diodes-division-vs-150ur120dm12.html>

### Request a Quote:

[Submit RFQ for this part](#)



Scan for product page

## Contact Information

Email: [info@antrexco.com](mailto:info@antrexco.com)

WhatsApp: +86-186-8066-5326

Website: <https://antrexco.com>

## Quality & Trust

New & Original Components

Supplier verification and packaging condition review

CoC / RoHS / REACH documents available on request

Secure sourcing support for OEM / EMS projects

### Note:

This PDF includes an ANTREX product reference cover page.

The original manufacturer datasheet follows from the next page.

---

## Standard Recovery Diodes, (Stud Version), 150 A



DO-8 (DO-205AA)

### FEATURES

- Diffused diode
- High voltage ratings up to 1200 V
- High surge current capabilities
- Stud cathode and stud anode version
- Hermetic metal case
- Designed and qualified for industrial level
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)


**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

- Welders
- Power supplies
- Machine tool controls
- High power drives
- Medium traction applications
- Battery charges
- Freewheeling diodes

### PRIMARY CHARACTERISTICS

|                       |                 |
|-----------------------|-----------------|
| $I_{F(AV)}$           | 150 A           |
| Package               | DO-8 (DO-205AA) |
| Circuit configuration | Single          |

### MAJOR RATINGS AND CHARACTERISTICS

| PARAMETER    | TEST CONDITIONS | VALUES      | UNITS             |
|--------------|-----------------|-------------|-------------------|
| $I_{F(AV)}$  |                 | 150         | A                 |
|              | $T_C$           | 125         | °C                |
| $I_{F(RMS)}$ |                 | 235         | A                 |
| $I_{FSM}$    | 50 Hz           | 3000        |                   |
|              | 60 Hz           | 3140        |                   |
| $I^2t$       | 50 Hz           | 45          | kA <sup>2</sup> s |
|              | 60 Hz           | 41          |                   |
| $V_{RRM}$    | Range           | 600 to 1200 | V                 |
| $T_J$        |                 | -40 to +180 | °C                |

### ELECTRICAL SPECIFICATIONS

#### VOLTAGE RATINGS

| TYPE NUMBER  | VOLTAGE CODE | $V_{RRM}$ , MAXIMUM REPETITIVE PEAK REVERSE VOLTAGE<br>V | $V_{RSM}$ , MAXIMUM NON-REPETITIVE PEAK REVERSE VOLTAGE<br>V | $I_{RRM}$ MAXIMUM AT $T_J = T_J$ MAXIMUM<br>mA |
|--------------|--------------|----------------------------------------------------------|--------------------------------------------------------------|------------------------------------------------|
| VS-150U(R).. | 60           | 600                                                      | 700                                                          | 15                                             |
|              | 80           | 800                                                      | 900                                                          |                                                |
|              | 100          | 1000                                                     | 1100                                                         |                                                |
|              | 120          | 1200                                                     | 1300                                                         |                                                |

**FORWARD CONDUCTION**

| PARAMETER                                                     | SYMBOL              | TEST CONDITIONS                                                                         |                      |                                                                       | VALUES | UNITS |
|---------------------------------------------------------------|---------------------|-----------------------------------------------------------------------------------------|----------------------|-----------------------------------------------------------------------|--------|-------|
| Maximum average forward current at case temperature           | I <sub>F(AV)</sub>  | 180° conduction, half sine wave                                                         |                      |                                                                       | 150    | A     |
|                                                               |                     |                                                                                         |                      |                                                                       | 125    | °C    |
| Maximum RMS forward current                                   | I <sub>F(RMS)</sub> | DC at 110 °C                                                                            |                      |                                                                       | 235    | A     |
| Maximum peak, one cycle forward, non-repetitive surge current | I <sub>FSM</sub>    | t = 10 ms                                                                               | No voltage reapplied | Sinusoidal half wave, initial T <sub>J</sub> = T <sub>J</sub> maximum | 3000   |       |
|                                                               |                     | t = 8.3 ms                                                                              |                      |                                                                       | 3140   |       |
| Maximum I <sup>2</sup> t for fusing                           | I <sup>2</sup> t    | t = 10 ms                                                                               |                      |                                                                       |        |       |
|                                                               |                     | t = 8.3 ms                                                                              |                      |                                                                       | 41     |       |
| Slope resistance                                              | r <sub>f</sub>      | T <sub>J</sub> = T <sub>J</sub> maximum                                                 |                      |                                                                       | 0.97   | mΩ    |
| Threshold voltage                                             | V <sub>F(T0)</sub>  |                                                                                         |                      |                                                                       | 0.80   | V     |
| Maximum forward voltage drop                                  | V <sub>FM</sub>     | I <sub>pk</sub> = 600 A, T <sub>J</sub> = 25 °C, t <sub>p</sub> = 10 ms sinusoidal wave |                      |                                                                       | 1.47   |       |

**THERMAL AND MECHANICAL SPECIFICATIONS**

| PARAMETER                                                | SYMBOL            | TEST CONDITIONS                               | VALUES          | UNITS |
|----------------------------------------------------------|-------------------|-----------------------------------------------|-----------------|-------|
| Maximum junction operating and storage temperature range | $T_J$ , $T_{Stg}$ |                                               | -40 to +180     | °C    |
| Maximum thermal resistance, junction to case             | $R_{thJC}$        | DC operation                                  | 0.3             | K/W   |
| Maximum thermal resistance, case to heatsink             | $R_{thCS}$        | Mounting surface, smooth, flat and greased    | 0.1             |       |
| Maximum allowable mounting torque + 0 - 20 %             |                   | Not lubricated threads tightening on hexagon  | 17              | N · m |
|                                                          |                   | Lubricated threads tightening on hexagon      | 14.5            |       |
|                                                          |                   | Not lubricated threads tightening on nut      | 14              |       |
|                                                          |                   | Lubricated threads tightening on nut          | 12              |       |
| Approximate weight                                       |                   |                                               | 130             | g     |
| Case style                                               |                   | See dimensions - link at the end of datasheet | DO-8 (DO-205AA) |       |

 **$\Delta R_{thJC}$  CONDUCTION**

| CONDUCTION ANGLE | SINUSOIDAL CONDUCTION | RECTANGULAR CONDUCTION | TEST CONDITIONS     | UNITS |
|------------------|-----------------------|------------------------|---------------------|-------|
| 180°             | 0.031                 | 0.023                  | $T_J = T_J$ maximum | K/W   |
| 120°             | 0.038                 | 0.040                  |                     |       |
| 90°              | 0.048                 | 0.053                  |                     |       |
| 60°              | 0.071                 | 0.075                  |                     |       |
| 30°              | 0.120                 | 0.121                  |                     |       |

**Note**

- The table above shows the increment of thermal resistance  $R_{thJC}$  when devices operate at different conduction angles than DC




Fig. 1 - Current Ratings Characteristics




Fig. 2 - Current Ratings Characteristics




Fig. 3 - Forward Power Loss Characteristics




Fig. 4 - Forward Power Loss Characteristics




Fig. 5 - Maximum Non-Repetitive Surge Current




Fig. 6 - Maximum Non-Repetitive Surge Current




Fig. 7 - Forward Voltage Drop Characteristics




Fig. 8 - Thermal Impedance  $Z_{thJC}$  Characteristic



ORDERING INFORMATION TABLE

|             |     |    |   |   |   |     |   |   |
|-------------|-----|----|---|---|---|-----|---|---|
| Device code | VS- | 15 | 0 | U | R | 120 | D | L |
|             | 1   | 2  | 3 | 4 | 5 | 6   | 7 | 8 |

- 1 - Vishay Semiconductors product
- 2 - 15 = essential part number
- 3 - 0 = standard device
- 4 - U = stud normal polarity (cathode to stud)
- 5 - None = stud normal polarity (cathode to stud)  
R = stud reverse polarity (anode to stud)
- 6 - Voltage code x 10 =  $V_{RRM}$  (see Voltage Ratings table)
- 7 - Diffused diode
- 8 - L = stud base 1/2"-24UNF-2A threads  
None = stud base 3/8"-24UNF-2A threads


Note

- For metric device M12 x 1.75 contact factory

| LINKS TO RELATED DOCUMENTS |                                                                        |
|----------------------------|------------------------------------------------------------------------|
| Dimensions                 | <a href="http://www.vishay.com/doc?95315">www.vishay.com/doc?95315</a> |

## DO-205AA (DO-8) for 150U(R) Series

**DIMENSIONS** in millimeters (inches)



### Note

<sup>(1)</sup> For stud base  $1/2\text{'-}20\text{UNF-}2\text{A}$  threads; refer to "Ordering Information Table"



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Vishay products are not designed for use in life-saving or life-sustaining applications or any application in which the failure of the Vishay product could result in personal injury or death unless specifically qualified in writing by Vishay. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.